

Sewing Pattern — Jeans 7065

Recommendations on fabric: denim with lycra

You will also need: fusible interfacing; 1 zipper; 1 button
If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Front – cut 2
2. Back – cut 2
3. Front facing – cut 2
4. Back facing – cut 1

Fusible interfacing: facings

INSTRUCTIONS:

1. Apply interfacing to wrong side of facings.
2. Pin fronts right sides together, sew center front seam from notch stopping 2 cm below step seam.
3. Press zipper opening seam allowances onto wrong side. Sew in the zipper.
4. Sew side and inside leg seams. Press seam allowances apart.
5. Insert on side of garment into the other, right sides together. Sew seam up to the upper edge. Press center seam allowances at the crotch.

6. Sew side seams of facings. Pin facing to garment upper edges, right sides together, and sew. Trim allowances to 0.5 cm width. Turn facings onto wrong side, press the upper edge. Turn facings short edges under, and slipstitch to zipper tape. Tack lower edges of facing to seam allowances.
7. Press the garment hem under, and sew along the edge. Fold the cuff along marking and sew it to side and inside leg seams.

TECHNICAL DRAWING:

