

Sewing Pattern — Blouse 7064

Recommendations on fabric: sheer knitted fabric

You will also need: fusible interfacing; 5 buttons.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

Fabric:

1. Collar – 2 folded pieces
2. Back part – 1 folded piece
3. Front part one-piece with front band – 2 pieces
4. Sleeve – 2 pieces
5. Cuff – 2 folded pieces

Interfacing: one-piece front band, outer collar, cuffs.

INSTRUCTIONS:

1. Apply the interfacing to wrong side of one-piece front band, outer collar, cuffs.
2. Stitch shoulder/side seams towards the mark, neaten them and press them apart.
3. Lay collars right sides together and overstitch them along outer side. Turn the collar right side out, process it neatly and press.
4. Neaten front band outer edge, fold it into right side and overstitch it along the neckline between edging's edge and collar mark. Slash neckline/front band seam near the mark stopping at 1 mm before the stitch. Fold front and into wrong side and press it.

5. Lay inner collar the garment right side together and stitch the collar in with 1 cm seam. Fold outer collar's lower edge under and topstitch it along joining seam.
6. Stitch sleeve edges together, neaten them. Stitch sleeves into armholes.
7. Fold cuffs along the center wrong side out and overstitch them along edges. Turn cuffs right side out and press them.
8. Fold cuff open edges under at 1 cm and topstitch them inserting sleeve hem between them.
9. Neaten garment hem allowance, turn it into wrong side and topstitch. Topstitch slits into side seams.
10. Make buttonholes into right edge, sew buttons on left one.

TECHNICAL DRAWING:

