

Sewing Pattern — Blouse 7061

Recommendations on fabric: viscose poplin

You will also need: fusible interfacing; 6 buttons

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Collar – 2 pieces
2. Stand-up collar – 2 pieces
3. Back part – 1 folded piece
4. Front part – 2 pieces
5. Sleeve – 2 pieces
6. Cuff – 4 pieces

Interfacing: edging placket, cuffs, collar, stand-up collar

INSTRUCTIONS:

1. Apply interfacing to wrong side of edging placket, cuffs, collar, stand-up collar.
2. Press edging one-piece placket into right side and overstretch lower edge. Stitch seam allowance perpendicular close to seam, stop 1 mm before stitches. Turn the placket right side out and press it.

3. Stitch darts. Stitch shoulder/side seams.
4. Press garment hem into wrong side, fold it under and topstitch it.
5. Process the collar along outer contour. Lay collar details right sides together inserting the collar between upper edges. Process the stand-up collar along front edges and one of upper edge. Stitch outer stand-up collar into neckline. Fold inner stand-up collar under and topstitch along joining seam. Make a buttonhole into stand-up right edge.
6. Stitch sleeve seam towards slit mark, press allowances apart. Make pleats into sleeve lower edge. Lay cuffs right sides together and process neatly along the contour. Stitch outer cuff to sleeve lower edge, fold inner one under and topstitch along joining seam.
7. Stitch sleeves in easing them along sleeve caps. Press sleeve joining seam's allowance at sleeve cap's segment towards the sleeve.
8. Make 5 buttons into right front part, make 1 buttonhole into each cuff. Sew buttons correspondingly.

TECHNICAL DRAWING:

