

## Sewing Pattern — Jacket 7054

Recommendations on fabric: fleece

You will also need: fusible interfacing; separable zipper

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



### **CUTTING:**

Fabric:

1. Off-set welt – 2 pieces
2. Upper sacking – 2 pieces
3. Lower sacking – 2 pieces
4. Center back part – 2 pieces
5. Side back part – 2 pieces
6. Side front part – 2 pieces
7. Collar – 2 pieces
8. Center front part – 2 pieces
9. Sleeve – 2 pieces

Interfacing: off-set welt, collar.

### **INSTRUCTIONS:**

1. Apply the interfacing to wrong side of off-set welt and collar.
2. Stitch middle back seam and back bulk seams.
3. Cut side front slit pockets with welts: press welts along the center right side out. Apply the stripe of fusing of 2 cm width to wrong side of pocket marking. Lay off-set welt and fabric lower sacking on front part, right sides together, pin them together along pocket entrance marking

and stitch. Lengthwise edges of facings coincides to pocket marking middle line! Cut the front part between stitches, cut the fabric diagonally at stitch ends. Do not cut facings! Press seam facing allowances apart. Fold facings into wrong side through the slit, then tack. Lay lower sacking on front part's wrong side on welt (lay sacking upward); topstitch the welt on right side along joining seam catching the sacking. Press sacking downwards. Turn small triangles at slit ends into wrong side and topstitch accurately between upper stitch ends and lower stitch ends. Cut sackings, adjust, and stitch them together.

4. Stitch front bulk seams. Stitch garment side/shoulder seams.

5. Lay outer collar on inner one and overstretch them along ends and flies. Turn the collar right side out and press it.

6. Stitch sleeve seams. Stitch sleeves into armholes.

7. Press closure allowance on edgings into wrong side and stitch the zipper under it.

8. Stitch inner collar on the garment right sides together. Press the seam towards the collar. Fold open edge of outer collar under and topstitch it along joining seam.

9. Press garment hem/sleeve hems into wrong side, fold under and topstitch them.

#### **TECHNICAL DRAWING:**

