

Sewing Pattern — Jacket 7052

Recommendations on fabric: fabric suitable for jackets and raincoats

You will also need: warmer; fusing; lining; Velcro

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

Fabric:

1. Back part – 1 folded piece
3. Off-set welt – 2 pieces
4. Sacking – 2 pieces
5. Front part – 2 pieces
7. Front band – 2 pieces
8. Collar – 2 pieces
9. Sleeve – 2 pieces

Lining:

2. Back part – 1 folded piece
6. Front part – 2 pieces
10. Sleeve – 2 pieces

Warmer: topstitch the warmer on back/front details, sleeves and outer collar along marking.

INSTRUCTIONS:

1. Apply the fusing to wrong side of off-set welt.
2. Cut side front slit pockets “in frames”: press welts along the center right side out. Apply the stripe of fusing of 2 cm width to wrong side of pocket marking. Lay off-set welt and sacking on front part,

right sides together, pin them together along pocket entrance marking and stitch. Lengthwise edges of facings coincides to pocket marking middle line! Cut the front part between stitches, cut the fabric diagonally at stitch ends. Do not cut facings! Press seam facing allowances apart. Fold facings into wrong side through the slit to make a neat frame, then tack. Lay sacking on front part's wrong side, on lower facing (lay sacking upward); topstitch lower facing on right side along joining seam catching the sacking. Press sacking downwards. Turn small triangles at slit ends into wrong side and topstitch accurately between upper stitch ends and lower stitch ends. Cut sackings, adjust, and stitch them together.

3. Stitch side/shoulder seams.

4. Lay outer collar on inner one and overstretch them along ends and flies. Turn the collar right side out and press it.

5. Stitch sleeve seams. Stitch sleeves into armholes. Press sleeve hems into wrong side.

6. Stitch lining details leaving unstitches segment into one of sleeves. Stitch front bands to lining. Lay the lining on garment right sides together and overstretch them along all edges inserting the collar between necklines of lining and the garment. Turn the jacket right side out and stitch unstitches segment. Sew sleeve lining hem to sleeve hem line neatly.

7. Stitch Velcro hooked piece on right edge, stitch Velcro napped piece on left one.

TECHNICAL DRAWING:

