

## Sewing Pattern — Jacket 7047

Recommendations on fabric: artificial suede/leather

You will also need: lining; 6 studs

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



### **CUTTING:**

#### Fabric:

2. Flap – 4 pieces
3. Upper pocket – 2 pieces
4. Upper pocket flap – 4 pieces
5. Back yoke – 1 folded piece
6. Middle back part – 2 pieces
7. Side back part – 2 pieces
8. Front yoke – 2 pieces
9. Side front part – 2 pieces
10. Center front part – 2 pieces
11. Front band – 2 pieces
12. Collar – 2 pieces
13. Upper sleeve – 2 pieces
14. Lower sleeve – 2 pieces

#### Lining:

15. Sacking – 4 pieces
16. Back part – 1 folded piece
17. Front part – 2 pieces
18. Upper sleeve – 2 pieces
19. Lower sleeve – 2 pieces

### **INSTRUCTIONS:**

1. Stitch middle back seam and relieve back seams. Topstitch seams at 2 mm.
2. Stitch back yoke to back part right sides together. Turn the seam towards the yoke and topstitch at 2 mm.
3. Stitch center front part to side front part except pocket entrance. Topstitch seams at 2 mm.
4. Fold flaps pieces right sides together and overstretch along side edges and lower edge, turn right side out and topstitch at 2 mm.
5. Coincide open edges of lower flap to edge of center front part's relieve, with the flap on center front part's right side and coinciding flap upper edge to notch. Lay upper sacking on the flap. Lay lower sacking on side front part's right side. Stitch the flap and sackings. Fold sackings into wrong side, adjust the, and stitch together. Topstitch flap's short edges on front part along decorative stitch.
6. Coincide upper flap's open edges to yoke edge, with flap on front yoke's right side. Lay upper sacking on the flap and tack then together. Lay lower sacking on lower front part's right side. Stitch the flap and sackings together. Stitch the yoke to front part. Fold sackings into wrong side, adjust them and stitch. Slash the seam near the pocket. Turn joining seam towards the yoke and topstitch.
7. Stitch side/shoulder seam of the jacket. Topstitch the seam at 2 mm.
8. Lay inner collar on outer one, right sides together, and overstretch them along ends and collar fall. Turn the collar right sideout and topstitch.
9. Stitch sleeve seams. Stitch sleeves into armholes according to marking. Fold sleeve hems into wrong side.
10. Stitch lining shoulder/side seams. Stitch lining sleeves' seams leaving one hole for turning out. Stitch sleeves into armholes. Stitch front bands to lining.
11. Lay the lining on the garment right sides together, inserting the collar between neckline edges, and overstretch along edgings, neckline and hem. Turn the garment right side out, fold lining sleeves' hems under and sew to garment's sleeve hems.
12. Make stud's upper parts into right front part, make lower parts into left front part.

**TECHNICAL DRAWING:**

