

## Sewing Pattern — Skirt 7045

Recommendations on fabric: denim with lycra

You will also need: fusible interfacing; zipper; 1 button; contrast threads for topstitching

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

### **Main fabric:**

1. Gusset – 2 pieces
2. Back facing – 1 folded piece
3. Right front facing – 1 piece
4. Button catch – 1 folded piece
5. Back skirt – 2 pieces
6. Patch pocket – 2 pieces
7. Right front skirt – 1 piece
8. Left front skirt – 1 piece
9. Left front facing – 1 piece
10. Belt loops – 1 piece

Interfacing: facings and button catch .

### **INSTRUCTIONS:**

1. Apply interfacing to wrong side of facings and button catch.
2. Stitch back darts and press them toward the center.

3. Stitch middle back seam up to the mark, stitch the gusset in, neaten seams and topstitch at 1 mm from edges.
4. Press pocket's upper edge into wrong side, fold edge under by 0.5 cm and topstitch at 1 mm from the edge. Press pocket allowances into wrong side and topstitch in on back skirts at 1 mm.
5. Neaten front skirt's middle edges, lay them right sides together and stitch middle front seam between fly front and 3-4 cm below.
6. Press one-piece facing on right skirt into wrong side along middle front edge, press one-piece left facing at 1 cm from the edge. Press button catch along the center right side out and neaten open edges. Stitch the zipper under closure left advance: zipper teeth are close to the bending; button catch lay under with its bending toward the middle so that neaten edge overlap zipper braid. Pin slit edges together coinciding middle front lines. Stitch zipper free braid to right facing; do not catch front skirt. Topstitch front skirt along the closure catching the facing and folding button catch out. Stop stitching 1.5-2 cm before middle seam. Fold button catch as before and continue stitching up to the seam.
7. Fold middle edge of right front skirt into wrong side and topstitch on left skirt. Stitch the gusset in, neaten seams and topstitch.
8. Stitch front facings to back ones along side edges. Press allowances apart. Neaten lower edge.
9. Lay facings on skirt's upper edge right sides together, and overstitch. Turn them right side out, fix short edges and topstitch upper edge at 1 mm.
10. Fold hem allowance into wrong side and topstitch.
11. Make a buttonhole into right front edge, sew a button on the left one.

**TECHNICAL DRAWING:**

