

Sewing Pattern — Trousers 7043

Recommendations on fabric: linen

You will also need: fusible interfacing; 1 zipper; Velcro

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Pocket facing – 2 pieces
2. Patch pocket – 2 pieces
3. Patch pocket flap – 4 pieces
4. Side front part – 2 pieces
5. Front sacking – 2 pieces
6. Upper front part – 2 pieces
7. Middle front part – 2 pieces
8. Lower front part – 2 pieces
9. Button catch – 1 piece
10. Upper back part – 2 pieces
11. Middle back part – 2 pieces
12. Lower back part – 2 pieces
13. Hem facing – 2 pieces
14. Waistband right part – 2 pieces
15. Waistband left part – 2 pieces

Fusing: waistband details, pocket facing, button catch, pocket flap.

INSTRUCTIONS:

1. Apply the fusing to wrong side of waistband details, button catch, pocket facings and the flap.
2. Tack pocket facings to front parts. Topstitch sackings to pocket entrances right sides together. Cut sacking joining seam allowances to 0.5-cm width. Turn sackings into wrong side. Turn lower edges under and topstitch them on front parts. Pin front parts on cut sides, then tack pocket entrance. Sew sackings together.
3. Overstitch flaps along figure edges, then turn into right side, press and topstitch along edges. Topstitch a piece of Velcro (with hooks) on flaps. Tack flaps on middle front parts according to marks. Topstitch Velcro soft pieces on pocket details. Make pleats into pockets, press pocket side allowances into, and topstitch it along marking on middle front parts of the garment.
4. Sew upper front part and middle front part (flap upper edge enter into joining seam). Press allowances upwards, then topstitch. Sew middle front part and lower front lower part (insert pocket lower edge into joining seam). Press allowances downwards.
5. Sew front parts right sides together under slit mark along front middle seam, stop sewing 2 cm before inside leg seam.
6. Press zipper closure one-piece facing into wrong side. Sew the zipper under left closure allowance. Sew zipper free band to right part to one-piece facing. Fold the button catch along the center its right side out, then neaten along long and short edges. Topstitch closure one-piece facing onto the zipper on the button catch (on garment left part). Topstitch slit right edge catching facing.
7. Sew upper back part to middle back part. Press allowances upwards, then topstitch. Sew middle back part to lower part. Press allowances into lower parts, then topstitch.
8. Sew inside leg and side seams. Sew back edge and front edge unsewn part with one stitch. Press allowances downwards roundings.
9. Sew waistband details in pairs, press seams apart. Sew waistband upper edge to garment upper edge right sides together. Press joining seam allowances to the waistband. Fold waistband upper and lower parts right sides together, then overstitch. Turn the waistband right side out, press it, and topstitch strictly along joining seam on right side. Topstitch hard piece of Velcro (with hooks) on waistband right end, and soft piece on the left one.
10. Sew hem facings into rings, then sew to garment hems right sides together. Turn facings into wrong sides and press. Topstitch facings on right side along the joining seam strictly.

TECHNICAL DRAWING:

