

Sewing Pattern — Raincoat 7029

Recommendations on fabric: proof fabric.

You will also need: flannel lining; separating zip (length depends on person's size); cord of 270 cm length; 2 wood buttons of 3 cm length; 2 decorative studs of 1 cm diameter; 1 tassel

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Upper front part – 2 pieces
2. Upper back part – 1 folded pieces
3. Hood – 2 pieces
4. Cuff – 2 pieces
5. Sleeve – 2 pieces
6. Placket – 2 pieces
7. Sacking – 2 pieces
8. Closure stripe – 4 pieces
9. Off-set welt – 2 pieces
10. Coulisse – 1 folded piece
11. Lower front part – 2 pieces
12. Lower back part – 1 folded piece

Lining: upper/lower front/back parts, sleeves, hood, sacking without changes.

INSTRUCTIONS:

1. Cut slit pockets with off-set welt into upper front parts: Fold the welt along the center wrong side out and overstitch short edges; turn right side out and press it. Pin downfolded welt on garment's right side as directed. Lay upfolded lining sacking on the welt and stitch at 5 mm

along both side of the mark. Cut the facing between stitches diagonally at stitch ends and turn sacking into wrong side. Topstitch welt's free edge on the sacking with zig zags. Fold both sackings, adjust them and stitch together along contours. Stitch welt's ends on the garment's right side and stitch sackings to front part.

2. Stitch upper front/back parts' side seams, Do the same for lower front/back parts.
3. Stitch sleeve seams and stitch sleeves into armholes. Press allowances frontward/backward, make decorative stitch.
4. Turn-in coulisse short edges and press the coulisse along the center right side out.
5. Pin the coulisse with its bending upward on garment's upper part.
6. Gather waist edge of lower part to make it equal upper part. Stitch waist edge joining the coulisse. Press allowances upward and make decorative stitch.
7. Stitch hood middle seam, press allowances apart and make decorative stitch along both side of the seam.
8. Make buttonholes into the hood.
9. Stitch the hood into neckline coinciding marks and shoulder seams.
10. Open the zipper. Pin sidefolded zipper parts on right side of front edgings.
11. Stitch lining details in the same way as fabric ones.
12. Stitch the garment to the lining right side together along hood front edge, front edgings (joining the zipper) and lower edge. Turn through the sleeve right side out and press.
13. Make fixing stitch along neckline joining the garment and the lining.
14. Make fixing stitch along hood front edge forming a coulisse.
15. Make double decorative stitch along garment's hem at 2.5 cm from lower edge.
16. Fold the cuff along the center wrong side out, stitch short edges, turn right side out, press and make decorative stitch along short edges/bending.
17. Stitch the cuff to sleeve hem with cuffs front edge on back one.
18. Fold lining hem under and sew to cuffs with blind stitches.
19. Lay stripes right sides together. Cut one of short edges as a corner and stitch along the perimeter excluding joining edge. Turn the detail right side out, press it and make decorative stitch.
20. Pin stripes with their corner in on one of right plackets' right side.
21. Stitch right plackets right sides together along rounded edge joining stripes. Turn right side out, press and make decorative stitch.

22. Lay the placket with its bending to side seam on right front part's right side. Stitch, press forward and make 1 cm fixing stitch.
23. Make buttonholes into stripes, sew buttons on left front edging.
24. Pull the cord into hood coulisse.
25. Sew the tassel in the center of hood middle seam.
26. Set decorative studs into cuffs.

TECHNICAL DRAWING:

