

Sewing Pattern — Bag 3009

Recommendations on fabric: stiff natural/mixed fabric (cotton velvet, fabric suitable for suits).

You will also need: fusing, lining, 2 concealed zips.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all.

Attention! Before sewing, print paper patterns and lay them out according to the linen width (from 90 to 150 cm) to find out how much material you need (do not forget about double and symmetric details).

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Main part – 2 pieces
2. Upper part – 2pieces
3. Handle – 1 piece

Lining:

1. Main part – 4 pieces

Fusing: main/upper part, handles.

INSTRUCTIONS:

1. Apply the fusing to wrong side of main/upper part and handles.
2. Fold the handle along the center wrong side out, overstitch long edge. Turn the detail right side out and press it. Make stitching at 0.2 cm from the edge. Fold short edges under and topstitch on main parts.
3. Lay main part on the lining right sides together, insert the zipper between them. Stitch close to zipper teeth. Stitch zipper another part between upper part and lining main part. Do the same for another main part and the zipper.
4. Stitch upper parts' lower edges together.

5. Stitch lining/fabric side edges between lower part and the zipper. Stitch side edge between upper part and the second mark straightening the zipper.
6. Stitch main parts' lower edges. Fold bag's corner: side seam and lower seam above one another.
7. Stitch lining main parts' lower edges leaving a hole to turn the bag right side out. Fold bag's corner: side seam and lower seam above one another. Make stitching crosswise side/lower seams.
8. Turn the bag right side out. Stitch the hole

TECHNICAL DRAWING:

