

Sewing Pattern — Dress 4325

Recommendations on fabric: natural or mixed knit fabric of medium stretchiness in two colors

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: on hem — 3 cm, all other seams - 0.8 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Central back – 2 details
2. Side back – 2 details
3. Side front — 2 details
4. Sleeve — 2 details
5. Cuff — 2 details
6. Back facing — 2 details
7. Front facing — 2 details

Main fabric_1:

1. Central front — 1 folded detail
2. Front neckline facing — 1 detail

Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hem is stitched with double needle to save stretchiness.

INSTRUCTIONS:

1. Sew princess seams on back. Finish and press the seam towards center. Sew center edge of back. Finish seam.
2. Sew darts on central front. Cut depths off with serger.
3. Sew shoulder seams. Finish seams.
4. Serge lower edge of front neckline facing. Overstitch the neckline of central front part with facing. Turn the facing onto wrong side and attach along princess edges.
5. Sew center edge of back facing. Serge separately lower edges of front and back facings. Sew shoulder seams of the facings. (back facing is shorter than shoulder edge of front facing). Fold the facing with garment right sides together, fold central front part with side part on princess edge, placing it between side part and facing. Sew princess edges, overstitching the neckline at the same time. Press seam allowances to side edge. Turn facings onto wrong side, press and tack to seams.
6. Press seam allowances and serge them. Sew sleeve into armhole, leveling notches. Press seam allowances and serge them.
7. Sew side edge and edge of sleeve.
8. Fold cuff right sides together into ring and sew short edge, press seam allowances apart. Fold cuff in half lengthwise wrong sides together, set cuff into sleeve and stitch to lower edge. Serge seam allowances. Turn cuff right side out.
9. Serge hem of the dress, turn inside and topstitch.

TECHNICAL DRAWING:

