

Sewing Pattern — Tunic 4332

Recommendations on fabric: knitted fabric of light to medium stretchiness.

You will also need: 2 buttons

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: hem and hem of sleeve –2.0 cm; top edge of pocket - 2.5 cm; along the perimeter of carrier - 0 cm; all other seams - 0.7 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Main fabric:

1. Back – cut 1 on fold
2. Front — cut 1 on fold
3. Sleeve – cut 2
4. Collar – cut 1
5. Casing for drawstring- cut 1

Advice:

Knit fabric pieces are sewn together with special elastic, narrow zig-zag stitch, or can be serged using an overlock machine. Seam allowance on hem is stitched with double needle to save stretchiness.

INSTRUCTIONS:

1. Sew darts on front, press darts down toward the hem.
2. Serge edges of pocket, press top seam allowance onto wrong side, topstitch. Press side and lower sides of pocket onto wrong side, place on front according to marks and topstitch. Sew on a button.
3. Sew shoulder seams of back and front. Press seams towards back.
4. Sew collar into ring, press seam allowances. Fold collar in half lengthwise right side out and sew into the neckline, matching notches and stretching edge of collar. Seam of collar is near left shoulder seam. Press collar connecting seam.
5. Sew sleeve into open armhole, matching notches. Press seam allowances.
6. Sew edge of sleeve and side as one. Press seam allowances.
7. Serge hem of garment and lower edge of sleeve, turn under, press, and topstitch.
8. Make two round buttonholes for tie to exit at marks on front. Serge or finish long edges of casing. Sew short edges together. Pin or baste to inside of garment on marked line. Topstitch on the outside.
9. Cut a tie of desired length (approximately, hip circumference + 30 cm), width is 4 cm. Press tie in half lengthwise, wrong sides together. Then unfold and press longitudinal edges to fold line. Fold again on center line and topstitch tie at 0.1 cm from the edge. Thread tie through the casing.

TECHNICAL DRAWING:

