

Sewing Pattern — Coat 4384

Recommendations on fabric: fabric suitable for coats

You will also need: fusible interfacing; lining; 6 buttons; ready-made decorative loop; shoulder pads; sleeve heads

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams -1 cm; hem of the garment - 3 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Central back – cut 2
2. Side back – cut 2
3. Back inset – cut 2
4. Side front – cut 2
5. Front inset – cut 2
6. Central front – cut 2
7. Upper sleeve – cut 2
8. Lower sleeve – cut 2
9. Stand collar – cut 2
10. Front band facing – cut 2
11. Off-set welt – cut 2
12. Cuff – cut 2
13. Back neckline facing – cut 1

Lining:

1. Central back – cut 2
2. Side back – cut 2
3. Central front – cut 2
4. Side front – cut 2

5. Upper sleeve – cut 2
6. Lower sleeve – cut 2
7. Pocket sacking – cut 4
8. Hidden closure placket – cut 2

Fusible interfacing:

1. Central front – cut 2
2. Front inset – cut 2
3. Stand collar – cut 1
4. Front band facing – cut 2
5. Off-set welt – cut 2
6. Cuff – cut 2
7. Back neckline facing – cut 1
8. Hidden closure – cut 1

INSTRUCTIONS:

1. Apply interfacing to listed pieces.
2. Place off-set welts right sides together, and sew side edges. Trim in corners, turn off-set welt out and press. Make a decorative stitch along the contour at 0.7 cm from the edge. Sew pocket sacking to off-set welt.
3. Sew side inset to side front, press seam allowances apart. Put pocket sacking onto right side of side front, put pocket sacking with off-set welt onto central front right side downwards. Sew pocket sacking to seam allowance of pocket opening. Turn side front seam back and topstitch onto pocket sacking.
4. Sew side and central fronts and pocket sacking. Slash allowances at the ends of pocket opening, press side and central fronts' connection seam to center, pressing the pocket. Topstitch side edges of off-set welt onto side front.
5. Sew back middle edge, press apart the seam. Sew back inset to side back, press apart the seam. Sew central and side backs, press seams toward center.
6. Sew side and shoulder seams of the coat. Press seam apart.
7. Mark with three lines the closure slit on right side of right front band facing; first line is parallel to front band edge and goes at 1.5 cm from the front band edge when ready; second and third lines determine the closure length. Place interfaced lining onto right side of front band facing, right side downwards, matching the lining edge with marked line. Make a stitch at 0.5 cm from marked line along closure slit up to lines determining the closure length. Put second closure lining edge to edge to first lining connection stitch, and make a stitch at 0.5 cm. Check you stitched linings correctly, from the wrong side stitches must be parallel. Cut the opening through. Make slanting cuts at 1-1.5 cm from the end of closure slit. Turn out through the given slit, making a frame from interfaced lining; frame's width is equal to distance between stitches. Make a fastening stitch into lining connection seam. Press second lining piece toward inner edge of front band facing and make a fastening stitch at 0.1 cm from lining connection seam. Mark and serge buttonholes. Punch buttonholes on front band facing together with interfaced lining. Straighten and fasten ends of closure from wrong side with double back stitch. Sew edges of lining pieces. Make bartacks between each pair of buttonholes. The length of bartack is equal to frame width. Press front band facing.
8. Sew back neckline facing to front band facings, press seam apart.
9. Sew outer stand collar into neckline, and inner stand collar – into facing/front band facing neckline, clip into curves, press apart. Put front band facings onto the coat and sew front band edges and collar stand with one seam, inserting decorative loop into right side of stand collar. Trim seams in corners, turn garment right side out, press.
10. Sew front sleeve edge. Press apart seam.

11. Press cuff in half lengthwise right side out. Unfold cuff and sew outer side to lower edge of sleeve, press seam onto cuff. Sew elbow sleeve seam, sewing the cuff at the same time.
12. Sew sleeves into armholes, matching the notches. Sew shoulder pads and sleeve heads.
13. Sew seams on lining details, leaving an opening in right front sleeve seam. Place lining and coat right sides together and sew lining to inner edges of front band facings and back neckline facing. Press apart seam allowances of stand collar connecting seam and fasten close to seams. Stitch lower corner of front band, trim corners. Mark and press to wrong side hem of the garment. Overstitch hem with lining. Sew lining sleeves to inner cuff. Turn coat out through the sleeve opening, sew the opening closed.
14. Make a decorative stitch on right front, fastening hidden closure.
15. Sew buttons according to buttonholes.

TECHNICAL DRAWING:

