

Sewing Pattern — Blouse 4388

Recommendations on fabric: guipure, chiffon

You will also need: invisible zipper, 6 buttons, fusible interfacing; bias tape, decorative cord.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: lower part edge – 0 cm, all other seams – 1 cm.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric:

1. Upper back – cut 2
2. Upper front – cut 4
3. Central front – cut 1
4. Lower front2 – cut 1
5. Lower back2 – cut 2
6. Stand collar – cut 4
7. Cuff – cut 2
8. Neckline facing – cut 1

Chiffon:

1. Sleeve – cut 2
2. Lower front1 – cut 1
3. Lower back1 – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing to outer stand collars and cuffs.
2. Sew darts on front and back and press toward center. Serge middle edges of back.
3. Serge lower edge of neckline facing. Stitch upper edge of front, clip seam allowances and turn facing to wrong side.
4. Sew upper fronts, inserting central part between them. Then process upper front details as one detail.
5. Sew shoulder and side seams. Serge seam allowances and press them to back.
6. Sew lower front¹ and lower backs¹. Serge seam allowances and press them to back. Trim lower edge with bias tape. Serge middle edges. Sew back middle edge from mark down to hem. Process lower parts² the same way. Level upper edges of lower parts and sew to bodice. Serge seam allowance. Sew in zipper.
7. Cut decorative cord to button size. Place stand collars right sides together and stitch upper and middle edges, inserting cord loops. Trim seams, turn right side out, press. Sew outer stand collars. Turn inside allowance of inner stand collar and topstitch into connecting seam.
8. Serge sleeve edge. Sew sleeve edge to slit mark and press seam apart. Make a fastening stitch along slit. Fold cuff in half lengthwise and stitch two sides. Clip in corners. Turn cuff out and press. Make a gathering stitch on lower edge of sleeve and gather ruffle. Sew outer cuff to sleeve. Turn inside allowance of inner cuff and topstitch into connecting seam. Make a gathering stitch on sleeve curve and gather ruffle. Sew in sleeves. Serge seam allowances.
9. Serge buttonholes on cuffs and sew buttons. Fasten stand collars edge-to-edge with invisible stitches.

TECHNICAL DRAWING:

