

Sewing Pattern — Blouse 4389

Recommendations on fabric: fabric suitable for blouses

You will also need: 12 buttons, fusible interfacing.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: hem of blouse – 1.5 cm, all other seams – 1 cm.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric:

1. Back – cut 2
2. Front yoke – cut 2
3. Front – cut 2
4. Placket – cut 2
5. Stand collar – cut 2
6. Sleeve – cut 2
7. Cuff – cut 2

Fusible interfacing:

1. Stand collar – cut 1
2. Placket – cut 2
3. Cuff – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing to listed pieces.
2. Place stand collars right sides together and stitch outer edge. Start and end stitch exactly at marked line of stand collar connecting seam. Turn ready collar out and press.

3. Sew darts on back. Press seams toward center. Sew center back seam. Press seam to left side and serge.
4. Make and fasten bow pleats on front yokes. Sew yoke to front, press seam onto front and serge.
5. Press plackets in half lengthwise wrong side together. Sew outer edge of placket to front. Serge seam toward placket. Turn inside inner edge of placket and topstitch into connecting seam
6. Sew shoulder and side edges. Press seams to back and serge.
7. Sew outer stand collar into neckline, turn under the edge of inner collar and topstitch into connecting seam.
8. Serge sleeve edge. Sew sleeve edge from mark upwards and press seam apart. Make a fastening stitch along fold at 0.2 cm from the edge. Sew sleeves into armholes. Serge seam allowances and press to sleeve. Fold cuff in half lengthwise right side inside, and stitch two sides. Turn right side out, press. Sew outer side of cuff to sleeve, turn inside seam allowance of inner side of cuff and topstitch into outer cuff connecting seam.
9. Serge hem of blouse, press to wrong side and topstitch.
10. Serge buttonholes on right front, sew buttons on left front. Serge buttonholes and sew buttons on stand collar and cuffs.

Advice: You can wear the blouse with belt. Cut detail of desired width and length from main fabric (including seam allowances). Fold belt in half lengthwise right side together and stitch on contour, leaving an opening. Trim seams in corners, turn belt right side out. Sew the opening closed.

TECHNICAL DRAWING:

