

Sewing Pattern — Jacket 4114

Recommended fabric: wool, suiting.

You will also need: lining, fusible interfacing

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: on hem and sleeve edges- 4.5 cm, other seams - 1 cm.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Main fabric:

1. Back - cut 1
2. Front - cut 2
3. Yoke — cut 1
4. Back of sleeve — cut 2
5. Front of sleeve —cut 2
6. Back neckline facing – cut 1
7. Buttonstand –cut 2

Lining:

1. Back - cut 1
2. Front - cut 2
3. Yoke — cut 1
4. Back of sleeve - cut 2
5. Front of sleeve — cut 2

INSTRUCTIONS:

1. Apply fusible interfacing to buttonstand, back neck facing, and to hems.
2. Sew darts on front part. Press fold of darts toward hem. Sew yoke to back and front. Press seams towards yoke side.
3. Sew upper edge of sleeve. Press seam apart.
4. Sew the sleeve in open armhole. Press seam apart. Sew edge of sleeve and side edge with one seam. Press seams apart.
5. Sew and press apart shoulder edges of back neckline facings and buttonstands.
6. Lay buttonstand with facing onto front, right sides together, pin and sew buttonstand and the neckline. Understitch. Stitch lower buttonstand edges to front exactly on marked line of hem turning. Trim seam allowances in corners. Turn stand parts onto right side, straighten seams, press.
7. Sew lining pieces the same way as outer pieces, leaving an opening in left lower seam of sleeve for turning out. Sew lining to inner buttonstand edges and back neckline facing.
8. Sew lining to hem of the garment and hem of sleeve. Turn jacket onto right side. Slip stitch the opening in the sleeve closed.
9. Topstitch or sew decorative stitch at 1 cm off edge along buttonstand and neckline. Topstitch or sew decorative stitch at 5 cm off hem of sleeve.

Attention: Jacket front seams line up and can be fastened closed with a loop and button, frog, or other decorative closure if desired.

TECHNICAL DRAWING:

