

## Sewing Pattern — Dress 4111

Recommendations on fabric: knitted fabric of middle stretchiness of natural or mixed fibers

You will also need: decorative lace

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: on hem – 2 cm; along back part and front part neckline, back part and front part armholes, on front part and top front part cut edges - 1.5 cm; all other seams - 0.7 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Back part – 2 details
2. Front part – 1 detail
3. Upper front part – 1 detail

Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 – 0.8 cm. Seam allowance on turnup is stitched with twin needles to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

### **INSTRUCTIONS:**

1. Sew middle edge of back part, press seam onto left side and serge.
2. Make and fasten plaits according to markers on front part. Direct depths downwards.
3. Stitch top part of front part to front part with the elastic stitch on lockstitch machine. Slash seam allowances near marker, serge. Serge slit seam allowance on top front part, press onto wrong side and topstitch. Slash slit seam allowance on front part near edge neckline marker, serge, press onto wrong side and topstitch.

4. Sew shoulder and side edges, press seam onto back part and serge.
5. Serge seam allowances of back part and front part neckline, armholes seam allowances of back part and front part, press onto wrong side and topstitch.
6. Serge hem of garment, press onto wrong side and topstitch.
7. Sew decorative lace to slit edges.

**TECHNICAL DRAWING:**

