

Sewing Pattern — Blouse 4109

Recommendations on fabric: silk or silk-like dress fabric of natural or mixed fibers.

You will also need: lightweight fusible interfacing, bias tape, 1 button

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: on hem - 3.5 cm, other seams - 1.0 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Blouse Yoke Fabric:

1. Front yoke – cut 1
2. Back yoke –cut 2
3. Front neck facing — cut 1
4. Back neck facing — cut 2
5. Front yoke bottom facing — cut 1
6. Back yoke bottom facing — cut 1

Blouse Fabric:

1. Center back – cut 1
2. Side back – cut 2
3. Center front – cut 1
4. Side front – cut 2

Interfacing:

1. Back neck facing
2. Front neck facing
3. Back yoke bottom facing
4. Front yoke bottom facing

INSTRUCTIONS:

1. Apply interfacing to listed pieces.
2. Place front yoke bottom facing, right sides together, with front yoke. Sew lower edge. Clip into curves, turn facing under, and press.
3. Serge center edges of back yokes separately. Sew center seam from notch to bottom edge. Place back yoke bottom facing, right sides together, with back yoke. Sew lower edge. Clip into curves, turn facing under, and press.
4. Sew shoulder seams of yokes and of neck facings. Serge and press seams of yokes toward back. Press neck facing seams toward front.
5. For button-loop, cut a strip of bias 3 cm wide and 7 cm long. Fold the band in half lengthwise and sew at 0.3 from the fold. Trim seam allowances and turn right side out. Adjust the loop length and baste buttonhole loop on right back yoke.
6. Press outer edge of the neck facings 1 cm inwards or serge. Sew the facing to the neckline, right sides together, sew center edge of back facing to center back seam at the same time. Trim corners and clip into curves. Press and undersew. Turn facing under and press. Tack at shoulder seams.
7. Sew sides fronts to center front. Serge seams and press toward center. Make a gathering stitch and gather between marks on center front.
8. Sew front to front yoke facing,,matching marks. Serge and press facing and front seam up towards yoke. Topstitch at 2.5 cm from the lower edge of the yoke, creating a lip.
9. Sew side backs to center back. Serge seams and press toward center.
10. Sew back to back yoke facing, matching marks. Serge and press facing and back seam up towards yoke. Topstitch at 2.5 cm from the lower edge of the yoke, creating a lip.
11. Cut (or use ready-made) bias tape of 4 cm wide for armhole. Fold bias tape in half lengthwise, wrong sides together, and press. Sew bias tape on right side of armhole edge. Turn bias tape to wrong side and topstitch along the fold onto garment.
12. Sew side seams. Serge seams and press toward back. Tack side seam allowance to armhole with 2-3 stitches.
13. Press bottom edge of garment under at 1 cm, then turn under again at 2.5 cm and topstitch.
14. Sew a button on back left, matching up with placement of button-loop on right.

TECHNICAL DRAWING:

