

Sewing Pattern — Blouse 4105

Recommended fabric: well draping knit fabric

You will also need: knit trim or bias tape 4-5 cm wide for finishing (the length is mentioned on the printed pattern), 2 small buttons.

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: along back neck and of front neck– 1.5 cm; seam allowance along the short edge of decorative panel – 2 cm; all other seams 0.7 cm.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.



Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.

CUTTING:

(The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Back — cut 1
2. Front – cut 1
3. Upper left front – cut 1
4. Sleeve – cut 2
5. Cuff – cut 2
6. Lower panel (band) – cut 1
7. Decorative panel– cut 1

INSTRUCTIONS:

1. Serge, press onto wrong side, and topstitch seam allowance of front and upper left front neckline.
2. Make evenly distributed pleats along the diagonal edge of front according to technical drawing, matching edge of front with lower edge of upper left front. Sew together front and upper left front, serge and press.

3. Serge edge of back neckline. Pin together shoulder edges of back and front, fold back neck seam allowance over front and sew, serge and press. Topstitch back neck edge.
4. Sew sleeves into open armholes, serge and press.
5. Fold decorative panel right sides together and sew long sides. Turn panel onto right side and press, placing seam in the center of panel. Serge top short edge.
6. Sew side seam and sleeve seam with one stitch, inserting lower edge of decorative panel into left side seam, serge and press seam toward back. Fold the panel over the neckline, along seam of front, and tack to the wrong side.
7. Sew lower panel (band) into ring. Press seam open. Fold band in half, wrong sides together and press. Make a gathering stitch along the lower edge of the garment and gather fullness. Sew band to lower edge, serge and press. Seam of band is near left side seam.
8. Sew cuff into ring, press seam open. Fold cuff in half, wrong sides together. Make a gathering stitch along the lower edge of sleeve and gather fullness to match length of cuff. Sew cuff to lower edge of sleeve, serge and press seam allowances.

TECHNICAL DRAWING:

