

Sewing Pattern — Dress 4085

Recommended fabric: knit fabric, chiffon.

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: 1 cm on all edges. Hem – 1.5 cm.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

(The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Advice:

Knit fabric pieces are sewn together with special stretch-stitch or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

Main fabric:

1. Front – cut 1 on fold
2. Back – cut 2
3. Cuff – cut 2

Chiffon:

1. Sleeves –cut 2

INSTRUCTIONS:

1. Sew center back seam. Serge and press toward left.
2. Mark and sew darts on front. Press toward hem.
3. Sew sleeve front to front armhole. Serge seam and press.
4. Sew sleeve back to back armhole. Serge seam and press.
5. Cut bias tape from knit fabric of the length equal to the neckline. Fold bias tape in half lengthwise and press. Open and fold longer sides towards center and press. Fold again and press. Finish neckline with bias tape.

6. Sew side seam and sleeve seam as one. Serge and press toward back.
7. Sew cuff into a ring. Turn right side out, fold in half lengthwise, and sew to sleeve, right sides together.
8. Serge bottom edge of garment. Fold onto wrong side, press, and topstitch.

TECHNICAL DRAWING:

