

## Sewing Pattern — Jacket 4082

Recommendations on fabric: costume fabric of natural or mixed fibers; companion fabric – thick silk

You will also need: fusing; lining; thin shoulder pads; 1 button.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: all seams 1 cm; on hem of sleeve - 3.5 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### CUTTING:

#### Main fabric:

1. Central back part – 2 details
2. Side back part – 2 details
3. Side front part – 2 details
4. Central front part – 2 details
5. Buttonstand – 2 details
6. Back neckline facing – 1 detail
7. Upper sleeve part – 2 details
8. Lower sleeve part – 2 details
9. Top bow – 1 detail
10. Strap — 1 detail
11. Bottom facing of back part — 1 detail

#### Silk:

1. Lower bow — 1 detail

#### Lining:

1. Central back part – 2 details
2. Side back part – 2 details
3. Side front part – 2 details
4. Central front part – 2 details
5. Upper sleeve part – 2 details
6. Lower sleeve part – 2 details

**ATTENTION:** details of back part and of front part from lining are cut excluding the width of back part neckline facing, back part hem facings and buttonstands accordingly.

**Fusing:** buttonstand, back part neckline facing, back part hem facing, central front part, side front part, lower bow, hem of sleeve

### **INSTRUCTIONS:**

1. Apply fusing to details. Put extra fusing selvage along front part neckline.
2. Sew dart on central front part. Press the dart upwards. Sew and press apart relieve edge on front part.
3. Sew dart on central back part. Sew and press apart relieves on back part. Sew and press apart middle seam of back part. Sew and press apart shoulder and side seams of the jacket.
4. Sew and press apart shoulder edges of back part and buttonstand neckline facings. Stitch back part hem facing to buttonstand. Press seams apart.
5. Fold strap in half lengthwise right sides together and overstitch on long side. Turn strap out and press, placing seam in the center of detail.
6. Fold top and lower bow details right sides together and overstitch top and lower sides. Straighten and press details. Lay bow one on another and fix on open edge.
7. Lay the strap according to markers on front part, placing strap seam atop and directing loose end towards side of the armhole. Topstitch strap on front part as marked. Stitch bows to neckline edge of right front part. Curve the bow with strap and stitch loose end to neckline edge.
8. Sew and press apart elbow sleeve seam, gathering slightly top part of sleeve and aligning notches. Press hem of sleeve. Turn hem allowance, sew and press apart front sleeve seam.
9. Sew sleeves into armholes according to notches, gathering rounding slightly on top. Stitch shoulder pads.
10. Sew seams on lining details and sew in sleeves, leaving a slit in left elbow seam for turning out. Stitch lining to inner buttonstand edges and facings.
11. Lay buttonstand with facing onto right side of front part right side downwards, pin together and overstitch buttonstand, front part neckline, back part neckline and hem of the jacket. Stitch from front part side. Topstitch buttonstand seam allowance onto buttonstand. Stitch on 0, 2 cm off the seam.
12. Stitch lining to hem of sleeve. Turn jacket onto right side. Sew a slit.
13. Serge a buttonhole on right front part, sew a button on left front part.

### **TECHNICAL DRAWING:**

