

## Snow Sport Pants - Sewing Pattern #4728

Recommendations on fabric: quilted raincoat fabric with polyester padding.

You will also need: lining, 2 hanks 3 cm wide, 2 hank belt buckles 3 cm wide, elastic tape 3 cm wide, elastic tape 0.7 cm wide, 1 zipper.

Seam allowances: Seam allowance along hem of pieces from self fabric – 5 cm, seam allowance along hem of pieces from lining fabric – 3 cm, other seams – 1 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

*Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.*



## CUTTING:

### Note on cutting:

*On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.*

*When sewing the garment, pay attention to notches, they must match up.*

Main fabric:

1. Front half - cut 2
2. Back half - cut 2
3. Decorative Tab - cut 2

Lining:

1. Front half – cut 2
2. Back half – cut 2
3. Fusing for elastic tape – cut 1

## INSTRUCTIONS:

1. Pin together front halves and sew center seam from notch to leg seam. Clip into seam allowance near notch. Sew in zipper.
2. Pin back halves together and sew center edge. Topstitch seam allowances onto left half at 0.1 - 0.2 cm from seam.
3. Sew side and leg seams. Topstitch side seam allowances onto back half.
4. Topstitch fusing for elastic tape onto self garment from the wrong side according to markings. Thread in elastic tape and fix the ends with machine stitch.
5. Fold decorative tab in half lengthwise, right sides together and sew. Turn decorative tab right side out and straighten it. Thread it through the hank and sew to the upper edge of front half according to markings.
6. Sew the 3 cm elastic tape to upper edge of back half according to markings. Thread the free end of the elastic tape through the hank buckle, then through the hank, then again through the buckle and fix it..
7. Sew the pieces from lining in the same way as you did for the pieces from self fabric.
8. Pin self to lining right sides together, the straps are turned inside. Fold away lining at 5 mm from edge of zipper and pin it to the upper edge of the jumpsuit. Fold seam allowances along zipper onto self fabric and pin them to upper edge on top of lining. Sew upper edges. Fold seam allowances along closure onto wrong side. Sew lining to zipper tape. Turn jumpsuit right side out and straighten it. Sew a decorative stitch at 0.8 cm along upper edge of jumpsuit and along zipper.
9. Turn jumpsuit right side out. Thread pant legs from lining into pant legs from self fabric. Turn hem on self fabric inside and press. Fold away seam allowance for hem. Match lower edge of lining to the fold line on self fabric from the wrong side. Lining should be placed between the self piece and the seam allowance for hem. Turn seam allowance for hem on self fabric under by 1.5 cm and topstitch from the wrong side. Total seam allowance for hem on self fabric is 5 cm, 1.5 cm turned under, and 3 cm visible..

## TECHNICAL DRAWING:

