

## Sewing Pattern — Blouse 4076

Recommendations on fabric: stretchy knit fabric of natural or mixed fibers

You will also need: fusing, 5 buttons.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: on garment hem and sleeve edges – 1.5 cm, other seams – 0.8 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

### **CUTTING:**

Fabric:

1. Front part – 1 folded detail
2. Back part - 2 details
3. Yoke – 1 detail
4. Sleeve – 2 details
5. Panel – 2 details
6. Ruche1 – 2 details
7. Ruche2 – 2 details
8. Ruche3 – 2 details
9. Stand-up part of collar – 2 details

Fusing:

1. Panel – 2 details
2. Stand-up part of collar – 1 detail

Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on turnup is stitched with twin needles to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.



### **INSTRUCTIONS:**

1. Sew darts on front part. Cut depths with a serger.
2. Sew middle cut of back part. Serge seam allowance and press it to the left side.

3. Sew the yoke to the back part. Serge seam allowances and press them downwards.
4. Sew shoulder seams. Serge and press towards back part.
5. Serge outer and lower edges of the ruche with a roll stitch. Put ruche2 with the right side on ruche3, put ruche1 on top. Put the stitch along inner edge of ruches with a loose top thread and gather ruffles. Stitch ruches to front part. Fold panels in half lengthwise and stitch to front part. Slash front part in corners according to markers. Turn seam allowances of the panel inside and fix with a stitch from inside. Stitch on panel on 0. 1 off the ruche connecting seam.
6. Fold stand-up parts of collar right sides together and overstretch on top edge. Begin and finish the stitch exactly near marked line of collar connecting. Sew outer stand-up part of collar in the neckline. Turn seam allowance of inner stand-up part inside and topstitch.
7. Sew sleeves in armholes, aligning notches. Serge.
8. Serge section from hem up to marker slit on front part. Sew edge of sleeve and side edges up to marker slit. Serge and press to back part.
9. Serge lower edge of sleeve. Turn onto wrong side, press and topstitch.
10. Serge lower edge of garment. Turn onto wrong side, press and topstitch. Press seam allowances along cuts onto wrong side and topstitch.
11. Serge loops on right front part; sew buttons on left one.

**TECHNICAL DRAWING:**

