

# Sewing Pattern — Dress 4072

<u>Recommendations on fabric</u>: knitted fabric of natural or mixed fibers.

You will also need: elastic yarn

If the pattern has double contour the seam allowances are included. Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: on hem -1.5 cm; along neckline -1 cm. Other seams - 0.7 cm

<u>Attention</u>! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### CUTTING:

### Main fabric:

- 1. Front part 1 folded detail
- 2. Back part 2 details
- 3. Upper sleeve part 2 details
- 4. Lower sleeve part 2 details
- 5. Inset 2 details
- 6. Cuff 2 details

### Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 - 0.8 cm. Seam allowance on turnup is stitched with twin needles to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

### **INSTRUCTIONS**:

- 1. Sew darts on front part. Cut depths with a serger.
- 2. Sew middle edge of back part. Serge and press onto left side.
- 3. Sew shoulder seams. Serge and press towards back part.
- 4. Serge front part and back part neckline. Turn seam allowances inside and topstitch.

5. Stitch loosely on top edge of inset and gather ruffles. Stitch inset to top part of sleeve. Serge. Stitch on inset with elastic yarn. Stitch loosely on top and lower edges of lower part of sleeve and gather ruffles. Stitch lower part of sleeve to inset. Serge.



6. Sew sleeve into armhole, leveling notches. Serge.

7. Sew side seams and edge of sleeve. Serge and press towards back part.

8. Sew cuff into ring. Fold in half lengthwise and stitch to the sleeve. Serge. Put stitches on cuffs with elastic yarn.

9. Serge lower edge of the dress. Turn onto wrong side, press and topstitch.

## TECHNICAL DRAWING:

