

Jacket With Slanted Closure - Sewing Pattern #4754

Recommendations on fabric: thin natural/mixed fabric suitable for coats.

You will also need: fusible interfacing; lining; thin shoulder pads; 4 buttons.

Seam allowances: all seams 1 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Center back – cut 2
2. Side back – cut 2
3. Side front right – cut 1
4. Side front left – cut 1
5. Center front right – cut 1
6. Center front left – cut 1
7. Lower back facing – cut 2

8. Back neck facing – cut 2
9. Lower front facing right – cut 2
10. Lower front facing left – cut 2
11. Front neck facing right – cut 2
12. Front neck facing left – cut 2
13. Upper sleeve – cut 2
14. Lower sleeve – cut 2
15. Upper cuff – cut 2
16. Lower cuff – cut 2
17. Strap – cut 2

Lining:

1. Center back – cut 2
2. Side back – cut 2
3. Side front right – cut 1
4. Side front left – cut 1
5. Center front right – cut 1
6. Center front left – cut 1
7. Upper sleeve – cut 2
6. Lower sleeve – cut 2

Fusible interfacing:

1. Lower back facing – cut 1
2. Back neck facing – cut 1
3. Lower front facing right – cut 1
4. Lower front facing left – cut 1
5. Front neck facing right – cut 1
6. Front neck facing left – cut 2
7. Upper cuff – cut 2
8. Lower cuff – cut 2

Attention! The pattern blocks are printed as seen from the right side. Turn them over when cutting from the wrong side of fabric!

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Serge separately, sew and press apart princess seams on the back (sew side backs to center backs). Sew and press apart center back seam. Sew lower facing to back, press towards facing and topstitch at 0.7 cm from seam. Sew neckline facing to back, press towards facing and topstitch at 0.7 cm from seam.
3. Sew darts on center fronts, press bulk towards top. Sew and press apart princess seams on front (serge

separately and sew center fronts to side fronts).

4. Left front: sew lower facing to front, clipping into seam allowance near corner. Press towards facing and topstitch at 0.7 cm from seam. Sew neckline facing to front, press towards facing and topstitch at 0.7 cm from seam. Right front: sew lower facing to front, clipping into seam allowance near corner, start stitching exactly at the marked line of neckline. Press towards facing and topstitch at 0.7 cm from seam. Sew neckline facing to front, stop stitching exactly at the marked line of center seam, press towards facing and topstitch at 0.7 cm from seam. Sew facings together, leaving unstitched the area between notches and thus forming a buttonhole. Press seam apart.

5. Sew and press apart shoulder and side edges.

6. Sew and press apart elbow sleeve seam, adjusting ease on upper part of sleeve and matching notches. Sew and press apart front sleeve seam. Sew cuffs together, press seam apart. Pin cuff onto sleeve right sides together and sew along lower edge. Press seam, fold cuff to wrong side and sew a decorative stitch at 0.7 cm from sleeve hem.

7. Pin together strap right sides together and sew along long side and one short side. Trim seam allowances, turn right side out strap onto right side, press and sew a decorative stitch at 0.7 cm from edge. Sew strap to inner side of cuff according to markings.

8. Sew sleeves into armholes matching notches, adjusting ease along upper side of sleeve cap. Sew shoulder pads.

9. Sew and press pieces from lining and inner neckline and hem facings in the same way as pieces from main fabric, leaving an opening for turning in left elbow seam of sleeve. Pin lining to self garment right sides together and sew around hem, center front and neckline. Trim away corners, clip into curves, turn garment right side out, press. Sew a decorative stitch around the contour at 0.7 cm.

10. Sew lining to hem of sleeve through the opening, press seam. Sew the opening closed.

11. Sew on button on left front. Make buttonhole on left front, sew on inner button on right front. Make buttonholes and sew on buttons on straps and sleeves.

TECHNICAL DRAWING:

