

Sewing Pattern — Blouse 4070

Recommendations on fabric: natural/mixed medium to high stretchy fabric.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 3.5 cm, hems — 1.5 cm, all other seams - 0.8 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.



When sewing the garment, pay attention to notches, they must match up with corresponding pieces.

Note on working with stretchy fabric: Knitted fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hems can be stitched with twin needles to save stretchiness. Pieces can also be sewn together with a serger.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric:

1. Upper front – cut 1
2. Lower center front – cut 1
3. Lower side front – cut 2
4. Back – cut 1
5. Side back – cut 2
6. Collar – cut 1
7. Front sleeve – cut 2
8. Back sleeve – cut 2

INSTRUCTIONS:

1. Sew center and side backs. Sew side and lower fronts. Serge seams and press them toward center.
2. Put gathering stitch along lower edge of upper front between triangle marks. Gather ruffle. Sew upper and lower fronts. Serge seam and press downwards.
3. Sew shoulder edges. Serge seams and press toward back.
4. Sew elbow seam of the sleeve. Serge seams and press them toward back part. Sew sleeve into open armhole, matching notches. Serge seam allowance.
5. Sew side edge and sleeve edge. Serge seam and press toward back.
6. Fold collar into ring with its right side inside and sew. Turn collar out, fold in half with its wrong side inside. Sew collar into neckline, matching notches. Side seam of the collar should be near the left shoulder seam. Serge and press collar connecting seam.
7. Serge hems, fold to wrong side and topstitch.

TECHNICAL DRAWING:

