

Sewing Pattern — Blouse 4063

Recommendations on fabric: silk fabrics of natural or mixed fibers

You will also need: elastic band 0,7cm wide

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: on hem - 1.5 cm; lower seam allowances of top parts - 1.5 cm; top seam allowances of lower parts - 1.5 cm; lower lining edges - 1.5 cm; other seams - 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Knitted fabric:

1. Upper front part – 1 folded detail
2. Upper back part – 2 details
3. Lower front part – 1 folded detail
4. Lower back part – 2 details
5. Front part lining- 1 folded detail
6. Back part lining– 2 details
7. Collar – 1 detail

INSTRUCTIONS:

1. Sew darts on lining details. Press depths towards center.
2. Serge middle edges of top back part and lining back part. Sew edges from notches downwards. Press the seam apart. Put the stitch along top part edges and lining edges on 0.2 cm off the edge.
3. Sew shoulder and side edges of top blouse part. Press seam allowances to back part. Sew shoulder and side edges of blouse lining. Press seam allowances to front part. Overstitch armhole of the blouse with lining twice over: first armhole of front part, then armhole of back part. Slash seam allowances and turn onto right side.
4. Stitch loosely on lower edge and neckline edge of top front part and gather ruffles. Fix top part with lining along neckline and lower edge.

5. Overstitch collar tails, cut in corners and turn onto right side. Slash seam allowances of outer edge of collar near the marker showing the start of sewing in the neckline. Stitch outer edge of collar to neckline. Turn seam allowance of collar inner edge inside onto wrong side and topstitch in collar top edge connecting seam.
6. Sew middle edge of lower back parts. Serge and press on left side. Sew side seams. Serge and press towards back part.
7. Sew top and lower parts of the garment. Serge, direct downwards and topstitch, making a self-belt y (leave a 2cm slit near left side seam) Run elastic band through the self-belt and fix ends.
8. Serge hem of garment. Turn onto wrong side, press and topstitch.

TECHNICAL DRAWING:

