

Sewing Pattern — Tunic 4058

Recommendations on fabric: shirting (cotton, viscose, polyester)

You will also need: fusible interfacing, 9 buttons, piping

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: hem of the garment – 1.5 cm, all other seams – 1cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Upper back - cut 1
2. Lower back - cut 1
3. Upper front - cut 2
4. Lower front - cut 2
5. Button-stand placket – cut 4
6. Sleeve – cut 2
7. Collar – cut 2
8. Collar-stand – cut 2
9. Strap – cut 4
10. Cuff — cut 2

Interfacing:

1. Collar – cut 1
2. collar-stand – cut 1

3. Button-stand placket – cut 2
4. Cuff — cut 2

INSTRUCTIONS:

1. Apply interfacing to plackets, cuffs, top collar and inner collar-stand.
2. Place top collar with lower, right sides together. Sew ends and outer edge of collar. Trim seams. Turn collar right side out, straighten, and press. Place collar-stand right sides together, insert ready collar between them, match notches and sew, sew ends of collar-stand at the same time. Start and end the stitch exactly near marked line of collar-stand connection seam. Turn ready collar out and press.
3. Make and sew pleats on upper front according to marked lines. Depths of pleats are turned toward button-stand, and folded edges turn toward side seam. Press pleats.
4. Sew darts on upper front. Press darts toward hem. On lower front, make and fasten soft pleats. Depths of pleats are directed toward center of front.
5. Make a gathering stitch on the top edge of lower back, and gather fullness. Sew side seams separately on upper and lower fronts and backs. Serge seams and press toward back. Sew upper and lower middle seam, inserting piping into the seam, if desired. Serge and press seam upwards.
6. Pin button-stand plackets right sides together, and sew outer edge. Turn plackets right side out and press. Sew outer placket to front. Press seam toward placket. Turn inner placket edge under, and topstitch into connecting seam.
7. Sew shoulder seams. Serge seams and press toward back.
8. Sew top collar-stand and collar into the neckline, turn edge of lower collar stand under, and topstitch into top collar-stand connecting seam.
9. Pin straps right sides together, and sew on long side and one short side. Turn right side out, press and stitch at 0.1 cm from the edge. Make buttonhole according to marking. On wrong side of sleeve, topstitch raw edge of strap exactly on marked lines.
10. Sew pintucks on sleeve: fold on marked line and stitch at 0.1 cm from the fold, press. Serge sleeve edges separately. Sew sleeve seam to notch. Press seam apart. Make a gathering stitch along sleeve cap for ease. Sew sleeve into armhole, matching notches and adjusting ease. Serge seam and press toward garment.
11. Fold cuffs in half lengthwise, right sides together, and sew sides. Start and end the stitch exactly near marked line of cuff connection. Turn cuffs right side out, out and press. Make a gathering stitch on lower edge of sleeve and gather fullness. Sew outer side of cuff to sleeve. Turn inner cuff seam allowance under, and topstitch into connecting seam.
12. Serge lower edge of garment, press onto wrong side, and topstitch.
13. Make buttonholes on right front, sew buttons on left front. Make buttonholes and sew buttons on cuffs. Sew buttons on right side of sleeve in center pintuck line.

TECHNICAL DRAWING:

