

## Sewing Pattern — Blouse 4057

Recommendations on fabric: natural / mixed blouse fabrics.

You will also need: 2 buttons

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: along the edge of the garment - 2 cm, on straight edges of sleeve – 2 cm, all other seams - 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Front part - 1 detail
2. Back part – 2 details
3. Sleeve – 2 details
4. Cuff – 2 details
5. Collar – 1 folded detail

### **INSTRUCTIONS:**

1. Mark and sew darts on front part and back part. Press depths towards center. Sew and serge side edges. Press seam allowances towards back part. Serge middle edge of back part. Sew details of back part from marker downwards. Turn seam allowance of unsewn section onto wrong side and topstitch on 0.1 cm off edge.
2. Turn straight edges of sleeve twice inside on 1 cm and topstitch. Fold cuffs in half right sides together and overstitch short sides exactly up to the sleeve connection line. Turn cuffs out and press. Stitch outer side of cuff to sleeve. Turn inner side of cuff and topstitch into connecting seam. Sew sleeve into armhole. Serge and press.
3. Stitch loosely on front part neckline (from marker up to marker) and gather ruffles. Fold collar in half right sides together and overstitch tails up to neckline connection line. Turn collar out and press. Stitch outer side of collar to neckline. Turn inner side of collar and topstitch into connecting seam.
4. Serge lower edge of the blouse, turn inside and topstitch.
5. Serge buttonholes on cuffs and sew buttons.

**TECHNICAL DRAWING:**

