

Sewing Pattern — Dress 4046

Recommendations on fabric: well draping knitted fabric of medium stretchiness

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: on hem, hem of sleeve, on neckline edge of inner part of front – 1.5 cm. Other seams - 0.8 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Knit fabric:

1. Back – 2 details
2. Upper front - 1 folded detail
3. Lower front - 1 folded detail
4. Inner part of front - 1 detail
5. Sleeve – 2 details

Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 – 0.8 cm. Hem seam allowance is stitched with twin needle to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

INSTRUCTIONS:

1. Sew darts on inner part of front. Press darts upwards. Serge seam allowance along neckline, turn inside and topstitch. Press detail.
2. Attach details of inner and of upper fronts on shoulder, side, lower edges and edges of the armhole. Then process as one-layer detail. Sew together upper and lower fronts. Press seam downwards.
3. Sew center edge of back. Press seam.
4. Slash seam allowance in corner on shoulder edge of front. Sew shoulder and side edges of back and of front. Finish seams and press them to back.

5. Sew center edge of collar. Sew collar into the back's neckline. Press seam. Finish open edge of upper front and press. Turn it inside and topstitch into collar connecting seam sewing.
6. Sew sleeve seam. Finish seam and press it towards back. Sew sleeve into armhole, leveling notches and easing in on rounded part. Finish seams and press them.
7. Serge hem of dress and hem of sleeve. Fold to wrong side, press and topstitch.
8. Wear the dress with belt.

TECHNICAL DRAWING:

