

Sewing Pattern — Dress 4022

Recommendations on fabric: natural or mixed knitted well draping fabric of medium stretchiness.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: on hem – 1.5 cm; lower edges of front part flounces and sleeves – 0 cm; all other seams - 0.7 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 2 details
2. Front part – 2 details
3. Collar – 2 details
4. Flounce of front part – 1 detail
5. Flounce of sleeve – 2 details

Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 – 0.8 cm. Seam allowance on turnup is stitched with twin needles to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

INSTRUCTIONS:

1. Sew center edge of back part, press seam onto left side and serge.
2. Serge lower edge of the front part flounce with thin rolled seam. Fold flounce in half lengthwise wrong sides together, insert it between front part details and sew center edge of front part. Press seam allowances onto left side and serge. Lay out the flounce, align upper edge of the flounce with upper edge of front part and fix. Stitch loosely along front part neckline edge between markers and gather ruffles.

3. Sew shoulder seams of back part and of front part. Press seam allowances towards back part and serge.
4. Sew each detail of collar into ring. Fold collars right sides together and overstretch upper edge. Turn ready collar out, straighten and press. Sew collar into the neckline, aligning notches, press and serge seam allowances.
5. Serge outer edges of sleeve flounces with thin rolled seam. Sew flounces into the armhole, press and serge seam allowances.
6. Sew side seams of back part and of front part. Press seam allowances towards back part and serge.
7. Serge hem of garment, press onto wrong side and topstitch.

TECHNICAL DRAWING:

