

Sewing Pattern — Dress 4008

Recommendations on fabric: natural / mixed silk fabrics

You will also need: fusing; blind zipper

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: front part neckline edge – 2 cm, along the hem of the garment – 2 cm, along the lower edge of front and back parts of sleeves -0 cm, along shoulder edge of sleeves near rounded part - 1 cm and it comes to 0 cm to lower edge. Other seams - 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Upper back part – 2 details
2. Lower back part – 1 folded detail
3. Upper front part – 2 details
4. Lower front part – 1 folded detail
5. Front part yoke — 1 detail
6. Back part yoke — 1 detail
7. Belt — 2 details
8. Front part of sleeve – 2 details
9. Back part of sleeve – 2 details
10. Front smaller part of sleeve – 2 details
11. Back smaller part of sleeve – 2 details
12. Back neckline facing — 1 detail

Fusing:

1. Back neckline facing - 1 detail

INSTRUCTIONS:

1. Apply fusing to the neckline facing.
2. Sew darts on upper back part. Press darts to center seam. Sew center edge of upper back part. Press and serge the seam. Serge outer edge of back part neckline facing. Overstitch the back part neckline with facing. Slash seam on rounded parts, turn the facing back and press.
3. Mark and stitch up 3 pleats on right side of upper front part. The ridge is directed to side seam. Press seam allowance along front part neckline twice at 1 cm. Turn first pleat back and topstitch seam allowance close to stitching up seam, placing the stitch under the pleat in such a way.
4. Stitch loosely at 0.5 cm off the edge along the lower edge of upper front part. Gather ruffles between notches. Sew upper front part to the yoke. Press seam downwards and serge.
5. Stitch upper back part to the yoke. Press seam downwards and serge.
6. Make 2 bow pleats on lower parts of the back / the front and fix them along top edge. Stitch loosely along top edge of lower back part / front part and slightly gather. Stitch lower back part and front part to corresponding details of the yoke. Press seam upwards and serge.
7. Fold details of the belt in half lengthwise right sides together and overstitch long and slanting edges. Turn the belt out and press. Stitch the belt to the front part yoke.
8. Sew shoulder seams, rounding the shoulder edge of front part with back part neckline facing. Serge, turn out and press seam allowances.
9. Sew right side edge, press seam onto back part and serge. Serge left side separately. Sew left side seam from the armhole up to top notch and from lower notch up to hem. Sew in the zipper between notches.
10. Sew lower edge of sleeve. Serge and press the seam to back part. Serge hem of sleeve and shoulder edges of sleeve from rounded part up to hem of sleeve with thin rolled seam. Sew the section of shoulder seam on the sleeve from rounded part up to the notch. In the same way overstitch smaller details of the sleeve and fix them along rounded part to bigger ones.
11. Sew sleeves into armholes. Serge and press the seams.
12. Turn lower edge of the dress twice inside at 1 cm and topstitch.

TECHNICAL DRAWING:

