

Sewing Pattern — Blouse 4002

Recommended fabric: fabric suitable for blouses (cotton, viscose, polyester).

You will also need: invisible zipper, thread in contrast color for decorative stitching, 7 buttons.

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: 1 cm on all edges, hem – 2 cm, sleeve hem – 2 cm

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

- 1.Back yoke – cut 1
- 2.Back – cut 2
- 3.Front – cut 2
- 4.Side – cut 2
- 5.Facing/button-stand – cut 2
- 6.Upper sleeve – cut 2
- 7.Lower sleeve – cut 2
- 8.Collar – cut 2
- 9.Collar-stand – cut 2
10. Tie – cut 4

Fusible interfacing:

1. Collar – cut 1
2. Collar-stand – cut 1
3. Facing/button-stand – cut 2

INSTRUCTIONS:

1. Apply fusing to facing/button-stand, inner collar and inner collar-stand.
2. Pin collar right sides together, sew outer edges. Trim seam allowances. Turn collar right side out, adjust and press. Pin collar-stand, right sides together, inserting ready collar between them, match notches and sew, at the same time sew edges of collar-stand. Start and stop stitching exactly at the marked line of sewing in collar-stand. Turn the ready collar right side out and press.
3. Mark and sew darts on front, press toward hem.
4. Sew center back seam. Serge and press seam toward left. Make a decorative stitch 0.5 cm from the seam. Sew yoke to back. Serge and press seam upward. Make decorative stitch 0.5 cm from the seam.
5. Pin right side of facing/button-stand on to wrong side of front and sew center edge. Turn facing to the right side, fold the edge and topstitch onto front at 0.5 cm from the fold. Make decorative stitch along button-stand 0.5 cm from the edge.
6. Sew side to back, serge and press seam toward back. Make decorative stitch 0.5 cm from the seam. Sew side to front, serge and press seam toward front. Make decorative stitch 0.5 cm from the seam. Sew shoulder seams, serge and press toward seam toward back. Make decorative stitch 0.5 cm from the seam.
7. Sew collar-stand into neckline, fold the open edge of inner collar-stand and topstitch into connecting seam of outer collar-stand. Make decorative stitch 0.5 cm from the seam.
8. Fold ties in half lengthwise, right sides together, and sew the long and one short side. Trim corners, turn right side out, press. Make decorative stitch 0.5 cm from the seam.
9. Sew lower sleeve to upper sleeve, inserting ties in between, serge and press onto upper sleeve. Make decorative stitch 0.5 cm from the seam. Sew sleeves into armholes. Fold sleeve hem under at 1 cm, then again at 1 cm and topstitch.
10. Press bottom edge of blouse onto wrong side at 1 cm, then again at 1 cm and topstitch.
11. Make buttonholes on collar-stand and right front. Sew buttons on left.

TECHNICAL DRAWING:

