

## Sewing Pattern — Dress 5995

Recommendations on fabric: knit fabric of medium stretchiness; thin woolen fabric for collar (flounce)

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: all seams - 0.7 cm, center edge and outer edge of collar / flounce – 1 cm, on hem of the garment and hem of sleeve – 2 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Knit fabric:

1. Central back part – 2 details
2. Side back part – 2 details
3. Central front part - 2 details
4. Side front part – 2 details
5. Back part of sleeve – 2 details
6. Front part of sleeve – 2 details

#### Woolen fabric:

1. Collar – flounce - 4 details

#### Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 – 0.8 cm. Seam allowance on turnup is stitched with twin needles to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

### **INSTRUCTIONS:**

1. Sew princess seams on back part, press seam allowances towards center and serge. Sew center edge of back part, press seam onto left side and serge.
2. Sew princess edges of front part, press seam allowances towards center and serge.
3. Stitch back parts of sleeves to back part. Stitch front parts of sleeves to front part. Press seam allowances onto the sleeve and serge.
4. Sew top edges of sleeves. Press seam allowances towards back part and serge.

5. Sew center edges of collars / flounces. Fold collars right sides together and overstretch outer edge. Slash seam allowances, turn collar right side out. Sew lower collar into the neckline, slash seam allowances near the notch. Turn open inner edge of collar inside and topstitch into collar connecting seam
6. Sew center edge of front part, inserting collar – flounce into the seam. Serge seam allowances.
7. Sew lower edges of sleeves and side edges with one seam, press seam onto back part and serge.
8. Serge seam allowance of lower edge of the garment and of sleeve, press onto wrong side and topstitch.

**TECHNICAL DRAWING:**

