

## Sewing Pattern — Skirt 5993

Recommendations on fabric: thin natural/mixed costume fabric.

You will also need: fusing; blind zipper.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams - 1 cm, hem of the garment – 4 cm, center edge of the flounce and center edge of back part from top edge up to marker - 4 cm, inner edge of slit facings– 0 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Back part – 2 details
2. Front part – 1 detail
3. Back yoke – 2 details
4. Front yoke – 2 details
5. Flounce – 4 details
6. Slit facing – 2 details

Fusing:

1. Back yoke – 1 detail
2. Front yoke – 1 detail
3. Slit facing– 2 details

### **INSTRUCTIONS:**

1. Apply fusing to yokes and slit facing.
2. Sew darts on back part details, press depths towards center.
3. Fold flounces pairwise right sides together and overstretch curvilinear edge. Slash seam allowances. Turn flounce onto right side, straighten and press. Put decorative stitch along the edge

at 0.1 cm.

4. Slash away seam allowance of center edge of the flounce near pleats meeting point. Put flounce onto back part, fixing center edges and topstitch inner fold of lower pleat according to markers on back part. Turn flounce to center seam and topstitch outer fold of lower pleat (four layers of the flounce and a layer of back panel). Turn flounce back onto back part and topstitch inner fold of top pleat according to markers on back panel. Turn flounce to center seam and topstitch inner fold of top pleat (four layers of the flounce and a layer of back panel). Turn flounce back onto back part and fix along top edge.

5. Sew center edge of back part from top edge up to marker slit. Slash seam allowances near marker, press apart. Overstitch slit with facing from marker up to hem. Sew top seam allowance of the facing to allowance of center edge of back part, press seam allowances downwards. Serge center edges of back part with one seam with slit facing. Overstitch lower corner of the slit exactly along the marked line of hem turnup. Slash seam allowances away. Turn the facing onto wrong side, straighten lower corner.

6. Stitch yoke of back part to back panel, press seam allowances upwards. Stitch front part yoke to front panel, press seam allowances upwards.

7. Serge separately left side edges, sew from zipper marker up to hem. Press apart the seam, pressing the slit for zipper. Sew in zipper. Sew right side edge, press seam onto back part and serge.

8. Sew right side edge of inner yoke. Serge lower edge. Fold yoke with skirt right sides together and overstitch upper edge. Topstitch seam allowances onto inner yoke by 0.2 cm off the seam. Turn facings onto wrong side, press. Turn inside left side edges of inner yoke and sew to zipper tape. Topstitch inner yoke into outer yoke connecting seam.

9. Serge lower edge of the skirt, press onto wrong side and topstitch with 3.5 cm seam according to technical drawing, fixing the facing.

### **TECHNICAL DRAWING:**

