

Sewing Pattern — Jacket With Shawl Collar 5992

Recommendations on fabric: wool or semi-wool.

You will also need: fusing, 1 decorative button, 1 small button, lining, raglan shoulder pads.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams.



Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

Fabric:

1. Collar – 2 pieces
2. Side back part – 2 pieces
3. Middle back part – 2 pieces
4. Front part – 2 pieces
5. Front band – 2 pieces
6. Back neckline facing – 1 piece
7. Bottom facing for back part – 1 piece
8. Back sleeve part – 2 pieces
9. Front sleeve part – 2 pieces
10. Front sleeve part facing – 2 pieces
11. Back sleeve part facing – 2 pieces

Lining:

1. Front part – 2 pieces
2. Side back part – 2 pieces
3. Center back part – 2 pieces
4. Back sleeve part – 2 pieces
5. Front sleeve part – 2 pieces
6. Lower sleeve – 2 pieces

Fusing:

1. Front part – 2 pieces
2. Front band – 2 pieces
3. Back neckline facing – 1 piece
4. Upper collar – 1 piece

Attention: front and back parts from lining are cut out without the width of facing for back neckline, bottom facing for back part and front band correspondingly.

INSTRUCTIONS:

1. Apply fusing to details. Apply an additional fusing tape 1 cm wide along the front neckline.
2. Mark darts on front and back parts. Cut the front part along the side part stitching line. Stitch the darts and press them towards the center. Stitch the breast dart and dash the dart depth. Press the dart apart. Stitch the cut side to the front part. Press the seam downwards.
3. Sew and press apart curved seams on back part. Sew and press apart middle seam on back part.
4. Stitch the back sleeve parts to the back part. Stitch the front sleeve parts to the front part. Press the seams apart.
5. Stitch the shoulder and upper sleeve seams. Press the seams apart. Stitch in shoulder pads. Sew with one stitch the lower sleeve and side seams. Press the seams apart.
6. Put collar parts together wrong side out. Overstitch the outer collar edge. Cut the seam. Turn the collar out and press. Stitch the collar to the jacket. Press the seam.
7. Stitch and press the shoulder seams of the back neckline and front band facings. Stitch the bottom facing of the back part to the front band. Press the seams apart.
8. Sew together parts from lining and stitch in the sleeves, leaving a slit in the left sleeve lower seam. Sew lining to inner edges of bands and facings.
9. Put bands with the attached facings onto front part right sides together, pin together and overstretch, front neckline, back neckline and hem. Stitch from the front side. Topstitch seam allowance onto band facing 0.2 cm off the seam.
10. Stitch together sleeve hem facings from the upper edge up to the notch and shorter edges. Press the seams apart. Overstitch the cut and sleeve hem. Turn the facing out and press.
11. Stitch the lining to the sleeve facing. Turn the jacket out to the right side. Sew the slit in the left sleeve lower seam.
12. Make buttonholes on the front parts according to the button sizes. Sew on the decorative button on the left front part. Sew on the small button on the wrong side of the right front part.

TECHNICAL DRAWING:

