

## Sewing Pattern — Jacket with Decorative Bow 5991

Recommendations on fabric: natural/mixed costume fabric, well draping fabric for decoration.

You will also need: fusing; lining; 3 buttons; shoulder pads; sleeve heads.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 0 cm for two long and one short bow sides and facing, 3 cm for hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Back part – 2 pieces
2. Front part – 2 pieces
3. Back neckline facing - 1 piece
4. Front stand – 2 pieces
5. Upper sleeve – 2 pieces
6. Lower sleeve – 2 pieces
7. Facing - 4 pieces

#### Draper fabric:

Bow – 1 piece

#### Lining:

1. Back part – 2 pieces
2. Front part – 2 pieces
3. Upper sleeve – 2 pieces
4. Lower sleeve – 2 pieces

Attention! Back and front pieces are cut without back neckline facing and front stand correspondingly.

Fusing: front stand, facing, back neckline facing.

### **INSTRUCTIONS:**

1. Apply the fusing to wrong side of front stand, back neckline facing, facing.
2. Stitch back darts. Press darts toward middle seam. Stitch middle back seam. Press the seams leftward.
3. Stitch front darts. Slash seam allowances and press towards side edge.
4. Mark the cut with three lines on the right front part. Apply stitched bias tape from fusing to this area. Fold facing details along the center wrong side out and press them. Mark auxiliary line on facing, which is parallel to bending of facing for stitching. Sew facings to front part (stop stitching near parallel cut markings). Stitches must be parallel to each other (check on the wrong side). Slash the cut. Make diagonal notches at 1-1.5 cm from the cut ends. Turn facings right side out through this slit; place pressed bending of facings line-on-line. Fix the cut ends on the wrong side with double reverse stitch at corner bases. Press.
5. Neaten two bow longer edges and one shorter edge with an overlocker rolled seam. Stitch loosely along unsewn edge of the bow and gather ruffles.
6. Pin front stand to front part right sides together, and overstitch along edging and front neckline at 2-3 cm from neckline edge and inserting the bow on the right front part. Overstitching is done on the front part side. Sew lower edges of front bands to front part, strictly along hem line. Slash seams at corners. Turn edgings right side out, neaten the seams, press.
7. Sew jacket side/shoulder edges and press them apart.
8. Sew shoulder edges of facing of back neckline and front band, then press apart. Overstitch the front and back neckline edge. Turn the facing to the wrong side, neaten the seams and press.
9. Sew sleeve elbow seam and press it apart. Press sleeve hems under. Sew sleeve front seam and press it apart.
10. Sew sleeves into armholes coinciding notches. Sew shoulder pads and sleeve heads.
11. Sew lining details and sew lining sleeves in, with a slit in front right seam of a sleeve.
12. Sew lining to inner edges of front stand and back neckline facing.
13. Sew the lining to garment hem. Turn the garment right side out through slit in the sleeve. Sew the slit in the sleeve.
14. Make a buttonholes on the right front part and sew on buttons on the left one.
15. Let the bow through the cuts, arrange beautifully and attach to the jacket.

### **TECHNICAL DRAWING:**

