

## Sewing Pattern — Blouse 5976

Recommendations on fabric: double-sided knit fabric of medium or high stretchiness.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

**SEAM ALLOWANCE:** on hem, hem of sleeve, top edge of inset and top edge of collar – 1.5 cm, all other seams - 0.8 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Main fabric:

1. Back – 1 folded detail
2. Front – 1 folded detail
3. Sleeve – 2 details
4. Inset – 1 detail
5. Collar – 1 detail

Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hem is stitched with double needle to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

### **INSTRUCTIONS:**

1. Mark and sew darts on front. Press depths upwards.
2. Sew shoulder seams, serge seams and press them towards back part.
3. Serge top edge of inset, press and topstitch.
4. Sew collar into ring. Serge and press seam. Sew collar into the neckline, placing collar seam near left shoulder seam. Stitch inset to collar connecting seam, leveling notches. Serge and press seam.
5. Sew side seams. Serge seams and press them.
6. Sew sleeve seam, serge and press it. Serge Нижний hem of sleeve, press onto wrong side and topstitch. Sew sleeve into armhole. Serge and press seam.
7. Serge hem of garment and edge of collar. Turn onto wrong side, press and topstitch.

**TECHNICAL DRAWING:**

