

## Sewing Pattern — Dress 5975

Recommendations on fabric: natural or mixed well draping knit fabric of medium or high stretchiness

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: on hem, on armhole edges, along neckline – 1.5 cm, all other seams - 0.8 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

Lining details are cut using main fabric pattern pieces and are the vent's length shorter.



### **CUTTING:**

Main fabric:

1. Back part – 2 details
2. Front part yoke – 1 detail
3. Upper front part – 1 detail
4. Lower front part – 1 detail

**Our advice:** stitch jersey details with special elastic/zig zag stitches. If you use an overlock, cut seam allowances till 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity.

### **INSTRUCTIONS:**

1. Sew center edge of back part. Press seam allowances to left side and serge.
2. On upper front part stitch loosely on yoke connecting edge and gather ruffles. Stitch yoke, press seam onto yoke and serge.
3. On upper front part stitch loosely from right armhole edge up to mark and gather ruffles to the edge length from the armhole up to mark on lower front part. On lower front part stitch loosely from mark up to side edge and gather ruffles to the length of edge from mark up to side edge on upper front part. Sew together upper and lower front parts, press seam allowances and serge.
4. Sew shoulder and side edges, press seam onto back part and serge.
5. Serge hem of garment, armhole edges, neckline. Press onto wrong side and topstitch.

**TECHNICAL DRAWING:**

