

## Jacket With Hood And Pockets - Sewing Pattern #6137

Recommendations on fabric: natural/mixed knit fabric of small stretchiness in contrasting or similar color.

You will also need: knit band; separating zipper; 2 cord end caps; decorative cord.

Seam allowances: all seams 1 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

### Note on working with stretchy fabric:

Knitted fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hems can be stitched with twin needles to save stretchiness. Pieces can also be sewn together with a serger. When serging, cut seam allowances to 0.6 – 0.8 cm.



## CUTTING:

### Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric 1:

1. Upper back – cut 1 on fold

2. Upper front - cut 2
3. Hood - cut 2
4. Center hood - cut 1
5. Hood facing - cut 1
6. Upper sleeve - cut 2

Main fabric 2:

1. Center back - cut 1 on fold
2. Middle front - cut 2
3. Center back sleeve - cut 2
4. Center front sleeve - cut 2

Main fabric 3:

1. Lower back - cut 1 on fold
2. Lower front - cut 2
3. Front side - cut 2
4. Pocket bag - cut 4
5. Lower back sleeve - cut 2
6. Lower front sleeve - cut 2

Knit band:

1. Lower placket - cut 1
2. Cuff - cut 2

## **INSTRUCTIONS:**

1. Sew upper back to middle back, press towards top and serge. Sew middle back to lower back, press towards top and serge.
2. Sew pocket bags to lower fronts. Sew side fronts to front, sewing the pocket bag at the same time. Press seam allowances towards center, serge.
3. Sew upper front to middle front, press towards top and serge. Sew center front to lower front, press towards top and serge.
4. Sew shoulder and side seams, press towards the back and serge.
5. Sew side hoods to center hood, press seam allowances towards center part and serge. Install the eyelets according to the markings. Serge inner edge of hood facing. Pin facing onto hood and sew the outer edge. Clip into curves, turn facing onto wrong side. Topstitch hood facing onto self hood, making a casing.

6. Sew hood into neckline, press seam allowances towards hood and serge.
7. Serge edges center front facings. Serge one longer edge of the lower placket. Sew the unserged edge of the placket to the lower edge of the jacket, slightly stretching the placket. Sew in zipper. Wrap the zipper with the placket and topstitch into seam of zippers. Fold the placket inside and topstitch into the seam of the upper edge of the placket.
8. Sew middle back sleeve to lower back sleeve, press towards top and serge. Sew middle front sleeve to lower front sleeve, press towards top and serge. Sew upper sleeve to middle front sleeve, press towards top and serge. Sew upper sleeve seam, press towards back and serge. Sew the lower edge of sleeve, press towards back and serge.
9. Sew sleeves into armholes, serge and press.
10. Sew cuff into a ring. Fold cuff in half lengthwise right side out and press. Sew the cuff to the sleeve, adjusting the length of the sleeve cap, serge.
11. Thread the cord into the hood's casing.

## **TECHNICAL DRAWING:**

