

Raincoat With Yokes - Sewing Pattern #2703

Recommendations on fabric: natural/mixed fabrics suitable for outdoor jackets in contrasting or similar color.

You will also need: lining; separating zipper; decorative cord; 2 cord stops; 2 cord ends, 2 grommets; elastic tape.

Seam allowances: all seams 1 cm. Seam allowance along the lower edge of the garment - 2.5 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric 1:

1. Back - cut 1 on fold
2. Front - cut 2
3. Sleeve - cut 2
4. Casing - cut 1

Main fabric 2 :

1. Back yoke - cut 1
2. Front yoke - cut 2
3. Sleeve inset - cut 2
4. Center front facing - cut 2
5. Back neck facing - cut 1

Lining:

1. Back - cut 1 on fold
2. Front - cut 2
3. Sleeve - cut 2

Attention! the pattern pieces from lining are cut using the pattern pieces for the main fabric except for the width of the yokes and of the sleeve insets. And except for the width of the center front facing and back neckline facing.

INSTRUCTIONS:

1. Sew back yoke to yoke. Press seam allowance towards top.
2. Sew front yoke to front. Press seam allowance towards top.
3. Sew the sleeve inset to the sleeve, clipping into seam allowance near corner. Press towards inset.
4. Sew shoulder and side seams. Press the seam apart.
5. Install grommets on front. Pin casing onto front and onto back from the wrong side and sew along the marked lines.
6. Sew sleeve seam. Press the seam apart. Sew sleeves into armholes, press seam.
7. Sew shoulder seams of central front facings and facings. Press the seam apart.
8. Place center front facing onto front right sides together and sew along the center front edge, inserting zipper, at the same time sewing neckline. Seam Allowances along neckline clip, fold the central front facing towards wrong side and press.
9. Sew seams on lining, leaving an opening in left side seam.
10. Sew lining to the central front facings and to facing. Sew lining to the lower edge and to the lower edge of sleeve. Turn the jacket right side out through the opening. Press the seams. Thread in decorative cord and install the cord stops and the cord ends. Sew a stitch line at the lower edge of the sleeve, making a casing. Thread the elastic tape into the casing, adjust length and sew ends together. Sew the opening closed.

11. Sew a fixing stitch along the zipper at 1.5-2 cm from the edge.

TECHNICAL DRAWING:

