

Short Jacket With Trimming - Sewing Pattern #2728

Recommendations on fabric: thin natural/mixed suiting fabrics.

You will also need: lining; fusible interfacing; decorative tape; 10 buttons; shoulder pads; sleeve heads.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment and hem of sleeve - 3 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 2
2. Front - cut 2
3. Center front — cut 4
4. Back neck facing - cut 2
5. Upper sleeve - cut 2
6. Lower sleeve - cut 2
7. Flap - cut 4

Lining:

1. Back - cut 2
2. Front - cut 2
3. Upper sleeve - cut 2
4. Lower sleeve - cut 2

Fusible interfacing:

1. Center front — cut 2
2. Back neck facing - cut 1
3. Flap - cut 2

INSTRUCTIONS:

1. Apply fusible interfacing to corresponding pieces, and also to seam allowances along hem of garment and hem of sleeves.
2. Sew shoulder and waist darts on backs, press bulk towards center. Sew the center back seam, press the seam apart.
3. Sew darts on front, cut away the bulk of the dart leaving 1 cm, press towards center.
4. Pin the flaps together pairwise, right sides together, and sew along the outer edge, inserting the decorative tape. Trim seam allowances along the curves, turn the flap right side out and press. Make buttonhole on flap, serge upper edge. Sew flap to front along the marked line (the outer edge is directed towards the shoulder). Fold flap down and topstitch along the seam.
5. Sew shoulder and side seams, press the seam apart.
6. Sew the elbow seam of the upper and lower sleeves, and the vent corners, inserting the decorative tape. Press the seam apart . Press the elbow seam on the sleeve, snip into seam allowances, and press the vent. Sew a slanted fixing stitch along the vent of the sleeve. Press the hem of sleeve. Sew and press apart front sleeve seam. Sew sleeves into armholes matching notches, adjusting ease on sleeve cap. Sew shoulder pads, sew sleeve heads.
7. Sew seams on lining and sew in sleeves. press onto wrong side hem of jacket and hem of sleeve, sew lining to hem of jacket and hem of sleeve. Straighten the lining, baste with the garment along the open edges and treat as one piece in the future.
8. Sew the shoulder edges of the neckline facings on the back and on center front, press the seams apart. Pin together the center front and the facing, right sides together, insert the decorative tape between the pieces, and sew the center front edge, the neckline and the lower corner. Trim away corners, clip into curves. Turn the piece right side out, straighten seams, press.

9. Sew the outer part of center front and of the neckline facing to the garment, inserting the decorative tape into the seam, press seam allowances towards center part. Fold the seam allowance of the inner part of the center front and of the facing onto the wrong side, press, and topstitch into the seam of the outer part.

10. Make buttonholes on right front, sew on buttons onto left front. Sew on buttons on the vents of the sleeve and onto the front under the flaps.

TECHNICAL DRAWING:

