

Sewing Pattern — Dress 5960

Recommendations on fabric: light-weight fabric suitable for dresses, companion fabric

You will also need: lining; fusible interfacing; elastic of 0.5 cm wide; dress zipper.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: hem – 1.2 cm, on top edge of upper back – 1.5 cm, other seams - 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats, etc. from the pattern onto your fabric.

Fabric:

1. Upper back – 1 detail
2. Lower back – 1 detail
3. Upper front – 2 details
4. Lower front – 1 detail

Companion fabric:

1. Center back – 1 detail
2. Lower placket of bac – 1 detail
3. Center front – 1 detail
4. Lower placket of front – 1 detail
5. Front inset – 1 detail
6. Collar – 2 details
7. Stand collar – 2 details

Lining:

1. Upper front – 2 details

Interfacing:

1. Collar – 1 detail
2. Stand collar – 1 detail

INSTRUCTIONS:

1. Apply fusing to collar and collar.
2. Sew together upper and center backs, press seam onto center part and serge. Sew together center and lower backs, press seam onto center part and serge.
3. Press front inset crosswise wrong sides together. Place upper front part with lining and overstretch center edge, inserting the placket. Overstretch edge of the armhole. Slash seam allowances on rounded parts, turn detail right side out.
4. On upper front stitch a dart at 4 cm, press depth apart. Stitch loosely along lower edge and gather ruffles on marked section.
5. Sew together upper and center fronts, press seam onto center part and serge. Sew together center and lower fronts, press seam onto center part and serge.
6. Sew right side seam (seam allowance of upper edge back is 1.5 cm longer), press seam onto back part and serge. Serge separately left side edges, sew from mark down to hem, press seam apart. Sew in zipper. Serge seam allowance of upper back edge, press onto wrong side and topstitch. Topstitch elastic along top edge of back, slightly stretching it.
7. Sew side seams of lower plackets, press and serge seam allowances. Stitch lower placket to dress, press seam allowances upwards and serge. Serge hem of garment, serge to wrong side and topstitch.
8. Place upper collar with lower one right sides together. Overstretch ends and outer edge of collar. Cut off seams. Turn collar out, straighten and press. Place stand collar details right sides together, insert ready collar between them, level notches and sew, overstretching ends of stand collar at the same time. Start and end the stitch exactly near marked line of stand collar connecting seam. Turn ready collar out and press.
9. Sew upper stand collar with collar into the front neckline, turn under open edge of lower stand collar and topstitch into upper stand collar connecting seam. Press open seam allowances of upper and lower stand collars onto wrong side, sew stand collars together.

ADVICE: Dress can be worn with decorative belt when desired.

TECHNICAL DRAWING:

