

## Denim Dress With Patch Pocket - Sewing Pattern #2760

Recommendations on fabric: natural/mixed jeans fabrics.

You will also need: fusible interfacing; dress zipper.

Seam allowances: all seams 1 cm; seam allowance for hem of dress and hem of sleeve — 2 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

*Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.*



## CUTTING:

### Note on cutting:

*On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.*

*When sewing the garment, pay attention to notches, they must match up.*

Main fabric:

1. Center back - cut 2
2. Side back - cut 2
3. Back yoke - cut 2
4. Lower back - cut 2
5. Center front - cut 2
6. Side front - cut 2
7. Front yoke - cut 2

8. Lower front - cut 2
9. Pocket — cut 2
10. Sleeve - cut 2
11. Front neck facing — cut 1
12. Back neck facing — cut 2

Fusible interfacing:

1. Front neck facing — cut 1
2. Back neck facing — cut 2

## **INSTRUCTIONS:**

1. Apply fusible interfacing.
2. Sew princess seams on upper back, press seam allowances towards center, serge. Sew a decorative stitch along the seam at 0.1 cm. Sew yoke to back, press seam allowances at yoke and serge. Sew a double decorative stitch along the seam at 0.1 cm and 0.7 cm.
3. Sew darts on lower backs, press bulk towards center. Sew a decorative stitch along the seam at 0.1 cm. Sew upper back to lower back, press seam allowances towards top, serge.
4. Serge the center back edges separately. Sew the center back seam from zipper mark to hem, press the seam apart. Sew in zipper.
5. Sew princess seams on upper front, press towards center and serge. Sew a decorative stitch along the seam at 0.1 cm. Sew yoke to front, press seam allowances at yoke and serge. Sew a double decorative stitch along the seam at 0.1 cm and 0.7 cm.
6. Apply a strap of fusible interfacing to the pocket opening. Cut (or take ready) bias tape , its width should equal 4 cm and its length should equal the length of pocket opening + 4 cm. Fold bias tape in half lengthwise right side out and press. Pin the bias tape to the pocket opening from the right side and sew. Fold bias tape onto wrong side, clip into seam allowances and topstitch onto main piece along the seam. Press seam.
7. Sew darts on lower fronts, press bulk towards center. Sew a decorative stitch along the seam at 0.1 cm. Fold the upper edge, the vertical edge and the lower edge of the pocket onto the wrong side, press. Pin pocket at lower front according to markings and topstitch with double stitch at 0.1 cm and 0.7 cm. Sew upper front to lower front, press seam allowances towards top, serge.
8. Sew center front seam, press seam allowances towards left, serge. Sew a double decorative stitch along the seam at 0.1 cm and 0.7 cm.
9. Sew the shoulder seams and the side seams of the garment, press towards the back and serge.

10. Sew the shoulder seams of the neckline facings, press the seam apart. Serge the outer edge. Pin facing onto garment right side down and sew the neckline. Clip seam allowances, fold facing onto wrong side and press. Slipstitch facing to garment along the shoulder seam and the zipper tape.
11. Sew sleeve seam, press towards back and serge. Sew sleeves into armholes, serge and press.
12. Serge lower edge of garment and lower edge of sleeve, press onto wrong side and topstitch.

### TECHNICAL DRAWING:

