

Sewing Pattern — Sarafan 4271

Recommendations on fabric: light natural or mixed fabrics, chiffon

You will also need: elastic yarn of 0.7 cm wide (the approximate length is mentioned on the lower front part pattern)

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowances: hem – 1.5 cm, all other seams - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Front part – 1 folded detail
2. Back part – 1 folded detail

INSTRUCTIONS:

1. Sew darts on front part. Press depths downwards.
2. Sew right shoulder edge. Serge seam allowance and press it towards back part.
3. Cut bias tape of 4 cm wide and as long as back part neckline and front part neckline + 4 cm. Fold the bias tape in half lengthwise and press. Put the bias tape onto the neckline and stitch. Slash seam allowances. Turn the bias tape onto wrong side and topstitch.
4. Sew left shoulder edge. Serge seam allowance and press it towards back part.
5. Cut bias tape of 4 cm wide and as long as the armhole + 4 cm. Fold the bias tape in half lengthwise and press. Put the bias tape onto armhole and stitch. Slash seam allowances. Turn the bias tape onto wrong side and topstitch.
6. Sew side seams. Serge seam allowances and press them towards back part. Make barred ends on side seams near armhole line.
7. Sew the elastic into ring. Topstitch elastic between marked lines, stretching it.
8. Serge hem of the sarafan, turn edges inside and topstitch.

TECHNICAL DRAWING:

