

Sewing Pattern — Skirt 5936

Recommendations on fabric: Fabrics of natural or mixed fibers / jeans fabric

You will also need: fusible interfacing; 1 invisible zipper; 1 button

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance : all seams 1 cm, hem of the garment 3 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Back – cut 2
2. Front – cut 1
3. Waistband– cut 1

Fusible interfacing:

1. Waistband

INSTRUCTIONS:

1. Apply interfacing to waistband and seam allowances of vents.
2. Sew darts on back, press toward center, and topstitch at 0.1 cm from the seam.

3. Serge center back edges separately, serge the vent at the same time. Sew center back seam from zipper mark to vent edge. Press seam apart, as well as opening for zipper. Press seam allowances of vent toward left. Press right side of vent at 1 cm and topstitch. Tack seam allowances of vent with machine stitch. Sew in zipper.
4. Sew center front seam of back extensions, serge and press seam toward left. Topstitch at 0.1 cm from the seam.
5. Make pleats on front. Topstitch pleats 4 cm from the top edge.
6. Sew front to back, right sides together, along side and front edges. Serge and press seam toward back. Topstitch at 0.1 cm from the seam.
7. Press waistband, in half lengthwise, wrong sides together. Serge lower edge of inner waistband. Pin outer edge of waistband to skirt with right side extending beyond zipper for button. Sew to top of the skirt. Sew both short ends, right sides together. Trim corners and turn right side out. Topstitch at 0.1 cm from waistband connecting seam. Make buttonhole and sew a button.
8. Serge lower edge of the skirt, press onto wrong side, and topstitch.

TECHNICAL DRAWING:

