

Sewing Pattern — Skirt 5934

Recommendations on fabric: lightweight wool, decorative fabric for insets

You will also need: lining, fusible interfacing, 1 invisible zipper, 1 button

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

All seams 1 cm. hem of the garment 3 cm, hem of lining on patterns – 0 cm, seam allowance along edge of vent – 6 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Back– cut 2
2. Back yoke – cut 2
3. Back inset– cut 2
4. Front inset – cut 2
5. Front yoke – cut 1
6. Front – cut 1
7. Waistband – cut 1

Lining:

1. Front – cut 1
2. Back – cut 2

Fusible interfacing: waistband, vent

INSTRUCTIONS:

1. Sew back inset to back. Serge and press seam. Sew back yoke to back. Serge and press seam toward yoke, topstitch at 0.1 cm from the seam.
2. Trim 5 cm on left back along vertical edge of vent. Apply interfacing to both sides of back vent. From the right side, mark the center seam (fold of vent). Press left side along fold of vent. On right, press seam allowance under 6 cm. Serge center back edges separately. Serge seam allowances of vent. Sew center back seam from zipper marker to corner of vent. Trim corner of seam allowance of right vent. Press seam apart, press vent and sew seam allowances. Topstitch diagonally at the top of vent. Sew in zipper.
3. Sew front inset to front. Serge and press seam toward center. Sew front yoke to front. Serge and press seam toward yoke, topstitch at 0.1 cm from the seam.
4. Sew side seams. Serge and press seam toward back.
5. Sew, serge, and press lining pieces. Darts are made as soft pleats. Along center back edge of lining, sew only between notch and vent. Slipstitch seam allowances to zipper tape. Baste lining to garment along top edge.
6. Apply interfacing to waistband. Press in half, wrong sides together. Sew outer side of the waistband to top edge of the skirt, at the same time sew both short sides, right sides together (right side will extend beyond zipper for button). Turn seam allowance of inner waistband onto wrong side and topstitch into connecting seam of the waistband. Make buttonhole and sew button.
7. Serge lower edge of the skirt. Turn onto wrong side, press, and sew with invisible stitches. Turn hem on lining twice at 1 cm and topstitch.
8. Turn skirt wrong side out. Tack garment and lining along center seam, Trim rectangle on left of lining according to markers and trim corner. Turn edges under, and sew to sides of vent.

TECHNICAL DRAWING:

