

Sewing Pattern — Skirt with Tucks 5932

Recommendations on fabric: thin woolen natural or mixed fabrics.

You will also need: lining, fusing, 1 invisible zipper, 1 button.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 3 cm for the garment hem, 1 cm for all other seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back panel – 1 piece
2. Side back part – 2 pieces
3. Front panel – 1 piece
4. Side front part – 2 pieces
5. Waistband – 1 piece

Lining:

1. Back panel – 1 piece
2. Side back part – 2 pieces
3. Front panel – 1 piece
4. Side front part – 2 pieces

Fusing: waistband.

INSTRUCTIONS:

1. Apply fusing to the wrong side of the waistband and vents.
2. Serge the curved edges of the back panel and side back parts separately for each detail, serging the vent at the same time. Stitch the curved edges of the back part from the upper edge to the vent ending. Press seam allowance towards the back panel middle. Press the vent right side at 1 cm and topstitch.

Press vent seam allowances and stitch them together.

3. Make and pin pleats at the front panel. Stitch the front curved edges. Press seam allowances to the side parts and serge.

4. Serge left side front and back panel edges separately. Stitch the left side edge from the zipper notch down. Press seam allowances apart and press edges left for zipper. Stitch the zipper into the left side seam of the garment.

5. Stitch the right side seam, press the seam allowance to the back and serge.

6. Stitch the curved and side seams for the lining parts in the same way it was done for the part from the main fabric. Put the skirt and the lining together right side out. Stitch zipper allowances to the zipper tape. Pin the lining to the garment at the upper edge.

7. Fold and press the waistband lengthwise in half right side out. Serge the lower edge of the inner waistband part. Stitch the outer waistband part to the upper edge of the skirt, at the same time stitching around the waistband corners. Stitch the inner waistband edge precisely into the waistband attachment stitch. Whipstitch the button hole and sew on the button.

8. Serge the hem of the main garment, press it onto the wrong side and stitch with invisible seam. Serge the lining hem, fold and topstitch.

TECHNICAL DRAWING:

