

Sewing Pattern — Jacket 4268

Recommendations on fabric: natural or mixed light-weight suiting fabric.

You will also need: fusible interfacing; lining; 1 button; small shoulder pads, sleeve heads.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowances: all seams 1 cm, hem of the garment -3.5 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Center back – cut 2
2. Side back – cut 2
3. Side front – cut 2
4. Center front – cut 2
5. Collar - cut 2 on fold
6. Buttonstand/facing – cut 2
7. Back neck facing – cut 1
8. Sleeve – cut 2
9. Pocket facing - cut 4
10. Underlay piece - cut 2

Lining:

1. Center front – cut 2
2. Side front -cut 2
3. Center back – cut 2
4. Side back – cut 2
5. Sleeve – cut 2

*Center back and center front lining pieces are cut using main pattern pieces, except for the width of neck facing and buttonstand/facing correspondingly.

Interfacing: center front, buttonstand/facing, back neck facing, outer collar, pocket facing, hem of the jacket

INSTRUCTIONS:

1. Apply interfacing.
2. Sew darts on back and press towards center. Sew side backs to center backs. Clip into curves and press seams open. Sew center back seam and press open.
3. Cut center front part along pocket line, leaving 1.5 cm to cross marker. Match sides of the dart. Cut off seam allowance between round markers. Sew the dart and trim away the depth. Press apart the bust dart. Baste opening of pocket closed. Sew side fronts to center fronts. Clip into curves and press seams open.
4. Mark pocket location. Fold pocket facings in half wrong sides together and press. Mark secondary lines on facings. Mark secondary lines parallel to pocket opening. Stitch facings to front. Finish the stitches near parallel lines of pocket marking. Check that the stitching is correct on the wrong side (stitches must be parallel). Cut pocket opening section through on side front part. Make cross cuts at 1-1, 5 cm off the end of the pocket. Turn facings to wrong side through the opening, straighten edges. Fix ends of pocket from the wrong side with double back stitch at the base of the corners. Place underlay piece onto facings from the wrong sides and topstitch into connecting seam of the facings.
5. Sew shoulder and side edges of the jacket, press seams open.
6. Sew collars, right sides together, along ends and outer edge. Trim seam allowances in corners, and clip into curves. Turn collar out, straighten and press. Sew collar into the neckline.
7. Sew buttonstand/facing and back neck facing together. Align facing, right sides together, to garment front and neckline, leaving 1.5 cm to the edge of buttonstand. Trim away seam allowances in corners, clip into curves. Turn facing under, straighten seams and press.
8. Sew sleeve to sleeve lining, right sides together, along sleeve edge. Trim seam allowances, turn sleeve right side out. Sew a small sleeve head to the sleeve from wrong side. Baste the sleeve to lining along rounded part. Sew sleeve into armhole matching marks.
9. Sew seams on the lining pieces, leaving an opening in left side seam. Sew lining to inner buttonstand/facing edges and back neck facing.
10. Sew armhole in two steps: first front part, then back part. Stitch lining to hem of the jacket. Turn jacket out through the opening in side seam. Slipstitch the opening closed.
11. Make buttonhole on right front, sew a button on left front.
12. Sew shoulder pads to lining. (They can also be placed between lining and fabric previously).

TECHNICAL DRAWING:

