

Sewing Pattern — Dress 5905

Recommendations on fabric: dress fabric / silk

You will also need: elastic thread, lining

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: on hem - 1.5 cm, other edges - 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Advice:

Knit fabric pieces are sewn together with special stretch-stitch or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

Fabric:

1. Front – 1 detail on fold
2. Back – 1 detail on fold

Lining:

1. Front part - 1 detail on fold
2. Back part - 1 detail on fold

INSTRUCTIONS:

1. Sew side seams on main fabric. Serge seams and press toward back.
2. Sew side seams of lining. Serge seams and press toward back.
3. Place main fabric and lining right sides together and stitch on top edge. Turn right side out and press.
4. Serge hem of main garment and of lining (separately). Turn seam allowances to wrong side, press and topstitch.
5. Put stitches with elastic thread up to waist level. Distance between stitches is 1.5 cm.

TECHNICAL DRAWING: